VIA Labs, Inc.

Data Sheet

VL810
Super-Speed USB Hub Controller

November 20, 2009
Revision 0.80

Revision History

Rev	Date	Initial	Note
0.8	11/20/2009	DH	Initial external release

Table of Contents

Revision History 2
Table of Contents 3
List of Figures 4
List of Tables 5
Product Features 6
VL810 System Overview 7
Pinout 8
Pin List 9
Pin Descriptions 11
- **Signal Type Definition** 11
- **USB 3.0 Interface** 11
- **USB 2.0 Interface** 12
- **Analog Command Block** 12
- **Side Band signal and Miscellaneous** 12
- **Test Pin** 13
- **Power and Ground** 13

Electrical Specification 14
Package Mechanical Specifications 15

List of Figures

Figure 1 – VL810 Block Diagram 7
Figure 2 – VL810 Pin Diagram 8
Figure 3 – Mechanical Specification – QFN 88L 10x10x0.85 mm Package 15

List of Tables

Table 1 – VL810 Pin List 9

Product Features

VL810
Super-Speed USB Hub Controller

- **Compliant to USB 3.0 aka. Super-speed USB**
  - Compliant to Universal Serial Bus 3.0 Specification Revision 1.0
  - Compliant to Universal Serial Bus Specification Revision 2.0
  - One up-stream port supports Super-speed(SS), high-speed (HS) and full-speed (FS) traffic
  - Four down-stream ports support Super-speed(SS), high-speed (HS), full-speed (FS), and low-speed (LS) traffic
  - In-house USB PHY employing advanced CMOS process to consume less power
- **Support full functions of sideband signal**
  - Support both individual and gang mode for power enable and over current detection on each down-stream port
  - Support green and amber LED status indicator with automatic and manual mode control on each down-stream port
- **Misc**
  - 3.3 V and 1.0 V power supply
  - PLL embedded with external 25MHz crystal
  - Support external SPI flash for firmware upgrade
- **Software**
  - Support Microsoft Windows 7, Vista, XP, 2003, 2000, and ME
  - Support Mac OS 10.X
  - Support various Linux kernels
- **Physical**
  - QFN 88L green package (10x10x0.85 mm)
- **Certification**
  - TBD.
- **Applications**
  - Standalone Super-speed USB hub
  - Desktop/Notebook motherboard on-board hub
  - Desktop front panel hub
  - Docking system
  - USB hub compound device with keyboard, mouse, display, and printer …

VL810 System Overview

VIA Lab's VL810 is a low-power single chip USB 3.0 Hub controller designed for connecting four more USB devices from a host computer or another hub. Employing advanced CMOS process, its integrated in-house USB PHY enables VL810 to run in USB Super-Speed, High-Speed, and Full-Speed modes while consuming less power. VL810 based hub devices can work on Windows 7, Vista, XP, 2003/2000/ME, Mac OS X and various Linux kernels without additional driver. It is suitable for stand alone USB hub, desktop PC front panel hub, motherboard on-board hub, docking systems, and USB hub compound device with mouse, keyboard, display, or printer, etc.

With well-planned pinout and advanced process, VL810 based devices can enjoy easy layout and low working temperature in a very small housing. Full sideband signal pins are available for showing power enable, over current, and LED status control. The SPI interface can support external EEPROM/Flash for firmware upgrades or additional software enhancements. VL810 is available in QFN 88L green package (10x10x0.85 mm) to fit small form-factor design.

Figure 1 – VL810 Block Diagram

Pinout

Figure 2 – VL810 Pin Diagram

Pin List

Table 1 – VL810 Pin List

Pin	Pin Name	Pin	Pin Name
1	VSUSUSB	45	VSUS33
2	SSREXT	46	USBHPE1#
3	VCCA33SSM	47	USBHOC4#
4	SSTX3+	48	USBHOC3#
5	SSTX3-	49	USBHOC2#
6	VCCA10SSRX3	50	USBHOC1#
7	SSRX3+	51	COREPWRDN#
8	SSRX3-	52	EXTPWRON
9	VCCA33SS3	53	VDD
10	USBHP3+	54	VSUS33
11	USBHP3-	55	GANGMODE
12	VCCA33SS3	56	USBHGRN4
13	GND	57	USBHGRN3
14	SSTX4+	58	USBHGRN2
15	SSTX4-	59	USBHGRN1
16	VCCA10SSRX4	60	PEXRST#
17	SSRX4+	61	SMCLK
18	SSRX4-	62	SMDAT
19	VCCA33SS4	63	TESTEN
20	USBHP4+	64	VSUS33
21	USBHP4-	65	VDD
22	VCCA33SS4	66	VDD
23	SSTX0-	67	VDD
24	SSTX0+	68	SSTX1+
25	VCCA10SSRX0	69	SSTX1-
26	SSRX0-	70	VCCA10SSRX1
27	SSRX0+	71	SSRX1+
28	VCCA33SS0	72	SSRX1-
29	VCCA33SS0	73	VCCA33SS1
30	VCCA10USBD	74	USBHP1+
31	USBDREXT	75	USBHP1-
32	VCCA33USBD	76	VCCA33SS1
33	USBDP+	77	SSTX2+
34	USBDP-	78	SSTX2-
35	VDD	79	VCCA10SSRX2
36	VDD	80	SSRX2+
37	USBHMBR4	81	SSRX2-
38	USBHMBR3	82	VCCA33SS2
39	USBHMBR2	83	USBHP2+
40	USBHMBR1	84	USBHP2-
41	USBHPE4#	85	VCCA33SS2

42	USBHPE3#	86	VCCA10SSM
43	USBHPE2#	87	SSXI
44	VSUS33	88	SSXO

Pin Descriptions

Signal Type Definition

Name	Type	Signal Description
Input	I	A standard input-only signal
Output	O	A standard active driver
Input/Output	I/O	A bi-directional signal
Analog bias	A_{BIAS}	Analog bias or reference signal. Must be tied to external resistor and/or capacitor bias network
Power	PWR	A power pin
Ground	GND	A ground pin

USB 3.0 Interface

Pin Name	Pin #	I/O	Signal Description
SSTX0+	24	O	USB 3.0 UP Port Differential Transmit Data +
SSTX0-	23	O	USB 3.0 UP Port Differential Transmit Data -
SSRX0+	27	I	USB 3.0 UP Port Differential Receive Data +
SSRX0-	26	I	USB 3.0 UP Port Differential Receive Data -
VCCA10SSRX0	25	PWR	Analog 1.0V
VCCA33SS0	28,29	PWR	Analog 3.3V
SSTX1+	68	O	USB 3.0 DP1 Port Differential Transmit Data +
SSTX1-	69	O	USB 3.0 DP1 Port Differential Transmit Data -
SSRX1+	71	I	USB 3.0 DP1 Port Differential Receive Data +
SSRX1-	72	I	USB 3.0 DP1 Port Differential Receive Data -
VCCA10SSRX1	70	PWR	Analog 1.0V
VCCA33SS1	73	PWR	Analog 3.3V
SSTX2+	77	O	USB 3.0 DP2 Port Differential Transmit Data +
SSTX2-	78	O	USB 3.0 DP2 Port Differential Transmit Data -
SSRX2+	80	I	USB 3.0 DP2 Port Differential Receive Data +
SSRX2-	81	I	USB 3.0 DP2 Port Differential Receive Data -
VCCA10SSRX2	79	PWR	Analog 1.0V
VCCA33SS2	82,85	PWR	Analog 3.3V
SSTX3+	4	O	USB 3.0 DP3 Port Differential Transmit Data +
SSTX3-	5	O	USB 3.0 DP3 Port Differential Transmit Data -
SSRX3+	7	I	USB 3.0 DP3 Port Differential Receive Data +
SSRX3-	8	I	USB 3.0 DP3 Port Differential Receive Data -
VCCA10SSRX3	6	PWR	Analog 1.0V
VCCA33SS3	9,12	PWR	Analog 3.3V
SSTX4+	14	O	USB 3.0 DP4 Port Differential Transmit Data +
SSTX4-	15	O	USB 3.0 DP4 Port Differential Transmit Data -
SSRX4+	17	I	USB 3.0 DP4 Port Differential Receive Data +
SSRX4-	18	I	USB 3.0 DP4 Port Differential Receive Data -
VCCA10SSRX4	16	PWR	Analog 1.0V
VCCA33SS4	19,22	PWR	Analog 3.3V
VCCA33SSM	3	PWR	USB 3.0 Master Block Analog 3.3V

USB 2.0 Interface

Pin Name	Pin #	I/O	Signal Description
USBDP+	33	I/O	USB 2.0 UP Bus Data Plus (D+)
USBDP-	34	I/O	USB 2.0 UP Bus Data Minus (D–)
VCCA33USBD	32	PWR	Analog 3.3V
VCCA10USBD	30	PWR	Analog 1.0V
USBHP1+	74	I/O	USB 2.0 DP1 Bus Data Plus (D+)
USBHP1-	75	I/O	USB 2.0 DP1 Bus Data Minus (D–)
USBHP2+	83	I/O	USB 2.0 DP2 Bus Data Plus (D+)
USBHP2-	84	I/O	USB 2.0 DP2 Bus Data Minus (D–)
USBHP3+	10	I/O	USB 2.0 DP3 Bus Data Plus (D+)
USBHP3-	11	I/O	USB 2.0 DP3 Bus Data Minus (D–)
USBHP4+	20	I/O	USB 2.0 DP4 Bus Data Plus (D+)
USBHP4-	21	I/O	USB 2.0 DP4 Bus Data Minus (D–)

Analog Command Block

Pin Name	Pin #	I/O	Signal Description
SSXI	87	I	25M crystal input
SSXO	88	O	25M crystal output
VCCA10SSM	86	PWR	1.0V OSC VDDA
SSREXT	2	A_{BIAS}	Super speed connect to external resistor
USBDREXT	31	A_{BIAS}	High speed connect to external resistor

Side Band signal and Miscellaneous

Pin Name	Pin #	I/O	Signal Description
USBHMBR1	40	O	DP1 Amber LED Indicator
USBHMBR2	39	O	DP2 Amber LED Indicator
USBHMBR3	38	O	DP3 Amber LED Indicator
USBHMBR4	37	O	DP4 Amber LED Indicator
USBHGRN1	59	O	DP1 Green LED Indicator
USBHGRN2	58	O	DP2 Green LED Indicator
USBHGRN3	57	O	DP3 Green LED Indicator
USBHGRN4	56	O	DP4 Green LED Indicator
USBHPE1#	46	O	DP1 Power Enable
USBHPE2#	43	O	DP2 Power Enable
USBHPE3#	42	O	DP3 Power Enable
USBHPE4#	41	O	DP4 Power Enable
USBHOC1#	50	I	DP1 Over Current Indicator
USBHOC2#	49	I	DP2 Over Current Indicator
USBHOC3#	48	I	DP3 Over Current Indicator
USBHOC4#	47	I	DP4 Over Current Indicator
EXTPWRON	52	I	External power on
COREPWRDN#	51	O	Core power down
GANGMODE	55	I	Gang mode
SMCLK	61	OD	SM bus clock
SMDAT	62	OD	SM bus data
PEXRST#	60	I	System reset

Test Pin

Pin Name	Pin #	I/O	Signal Description
TESTEN	63	I	Test Mode Enable Do not connect for normal operation. Internal pull down.

Power and Ground

Pin Name	Pin #	I/O	Signal Description
GND	13	GND	Ground
VDD	35,36,53, 65,66,67,	PWR	1.0V Core power
VSUS33	44,45,54, 64,	PWR	3.3V suspend power
VSUSUSB	1	PWR	1.0V suspend power

Electrical Specification

Absolute Maximum Rating

Symbol	Parameter	Min	Max	Unit	Note
T_{STG}	Storage Temperature	-55	125	°C	—
T_A	Ambient Temperature	0	70	°C	—
V_{Sus33}	3.3V Power Supply Voltage	-0.5	3.69	V	—
V_{DD}	Input Voltage	-0.5	1.1	V	—
V_{SUSUSB}	Input Voltage	-0.5	1.1	V	—
V_{ESD}	Electrostatic Discharge	—	2	kV	Human Body Model

Note: Stress above conditions may cause permanent damage to the device.
Functional operation of this device should be restricted to the conditions described.

DC Characteristics

Operating Conditions:
T_C = 0~+55°C
V_{DD} = 1.0 V±10%
V_{SUSUSB} = 1.0 V±10%
V_{SUS33} = 3.3V±10%
GND = 0V

Symbol	Parameter	Min	Max	Unit	Note
V_{IL}	Input Low Voltage	-0.50	0.8	V	—
V_{IH}	Input High Voltage	2.0	VCC+0.5	V	—
V_{OL}	Output Low Voltage	—	0.4	V	IOL=4.0mA
V_{OH}	Output High Voltage	2.4	—	V	IOH=-1.0mA
I_{IL}	Input Leakage Current	—	+/-10	μA	0<VIN<VCC
I_{OZ}	Tristate Leakage Current	—	+/-20	μA	0<VOUT<VCC

Package Mechanical Specifications

Symbol	Dimension in mm			Dimension in inch		
	MIN	NOM	MAX	MIN	NOM	MAX
A	0.80	0.85	0.90	0.031	0.033	0.035
A1	0.00	0.02	0.05	0.000	0.001	0.002
A2	0.60	0.65	0.70	0.024	0.026	0.028
A3	0.20 REF			0.008 REF		
b	0.15	0.20	0.25	0.006	0.008	0.010
D/E	10.00 BSC			0.394 BSC		
D1/E1	9.75 BSC			0.384 BSC		
e	0.40 BSC			0.016 BSC		
L	0.30	0.40	0.50	0.012	0.016	0.020
θ	0°	---	14°	0°	---	14°
R	0.075	---	---	0.003	---	---
K	0.20	---	---	0.008	---	---
aaa	0.10			0.004		
bbb	0.07			0.003		
ccc	0.10			0.004		
ddd	0.05			0.002		
eee	0.08			0.003		
fff	0.10			0.004		

Figure 3 – Mechanical Specification – QFN 88L 10x10x0.85 mm Package

VIA Labs, Inc.

7F, 529-1, Chung-Cheng Road,
Hsin-Tien, Taipei, Taiwan
Tel: (886-2) 2218-1838
Fax: (886-2) 2218-8924

Copyright © 2009 VIA Labs, Inc. All Rights Reserved.

No part of this document may be reproduced, transmitted, transcribed, stored in a retrieval system, or translated into any language, in any form or by any means, electronic, mechanical, magnetic, optical, chemical, manual or otherwise without the prior written permission of VIA Labs, Inc. The material in this document is for information only and is subject to change without notice. VIA Labs, Inc. reserves the right to make changes in the product design without reservation and without notice to its users.

All trademarks are the properties of their respective owners.

No license is granted, implied or otherwise, under any patent or patent rights of VIA Labs, Inc. VIA Labs, Inc. makes no warranties, implied or otherwise, in regard to this document and to the products described in this document. The information provided by this document is believed to be accurate and reliable as of the publication date of this document. However, VIA Labs, Inc. assumes no responsibility for any errors in this document. Furthermore, VIA Labs, Inc. assumes no responsibility for the use or misuse of the information in this document and for any patent infringements that may arise from the use of this document. The information and product specifications within this document are subject to change at any time, without notice and without obligation to notify any person of such change.