


# DTK COMPUTER INC. PTI-245

Card Type  
Hard Drives supported  
Floppy drives supported  
Data Bus  
Card Size

Hard drive controller card  
Two IDE (AT) drives  
Two 360KB, 720KB, 1.2MB, or 1.44MB drives  
32-bit VESA Local Bus  
Full-length, full-height card



CONNECTIONS				
Function	Location	Function	Location	
25-pin parallel port - external	CN1	10-pin serial port (1)	JP1	
34-pin cable connector - floppy drive	J1	10-pin serial port (2)	JP4	
40-pin connector IDE(AT) interface	J2			

USER CONFIGURABLE SETTINGS			
Function	Label	Position	
Parallel port is uni-directional	JP2	Closed	
Parallel port is bi-directional	JP2	Open	
Floppy drive interface enabled	JP3	Pins 19 & 20 closed	
Floppy drive interface disabled	JP3	Pins 20 & 21 closed	

IDE SPEED SELECTION	
Speed	JP6
Speed 0 (slow)	Pins 1 & 2, 4 & 5 closed
Speed 1 (fast)	Pins 2 & 3, 4 & 5 closed
Speed 2 (turbo)	Pins 2 & 3, 5 & 6 closed

PARALLEL PORT ADDRESS SELECTION	
Setting	JP3
LPT1 (378h)	Pins 13 & 14, 17 & 18 closed
LPT2 (278h)	Pins 14 & 15, 16 & 17 closed
LPT3 (3BCh)	Pins 13 & 14, 16 & 17 closed
Disabled	Pins 14 & 15, 17 & 18 closed

Continued on next page . . .

. . . continued from previous page

SERIAL PORT 1 ADDRESS SELECTION	
Setting	JP3
COM1 (3F8h)	Pins 1 & 2, 5 & 6 closed
COM3 (3E8h)	Pins 2 & 3, 4 & 5 closed
Disabled	Pins 2 & 3, 5 & 6 closed

SERIAL PORT 2 ADDRESS SELECTION	
Setting	JP3
COM2 (2F8h)	Pins 7 & 8, 11 & 12 closed
COM4 (2E8h)	Pins 8 & 9, 10 & 11 closed
Disabled	Pins 8 & 9, 11 & 12 closed

BIOS ADDRESS SELECTION	
Setting	JP5/Pins 5 & 10
Enable	Closed
Disable	Open

PARALLEL PORT INTERRUPT SELECTION	
IRQ	JP3
IRQ7	Pins 22 & 23 closed
IRQ5	Pins 23 & 24 closed