MAXTECH CORPORATION
E N - 4 3 0 0

NIC Type	Ethernet
Network Transfer Rate	10Mbps
Data Bus	32-bit VESA Local Bus
Topology	Linear Bus, Star
Wiring Type	Unshielded twisted pair (location unidentified) RG-58A/U 50ohm coaxial (location unidentified)
Boot ROM	Available (location unidentified)

Diagram not available

USER CONFIGURABLE SETTINGS		
Function	Label	Position
í Jumperless mode	JP3	Pins 1 & 2 closed
Jumpered mode	JP3	Pins 2 & 3 closed

BASE I/O ADDRESS SELECTION			
Address	J0	J1	J2
Software	Closed	Open	Open
240h	Open	Closed	Open
280h	Closed	Closed	Open
2C0h	Open	Open	Closed
300h	Open	Open	Open
320h	Closed	Open	Closed
340h	Open	Closed	Closed
360h	Closed	Closed	Closed

INTERRUPT SELECTION			
IRQ	J3	J4	J5
2	Closed	Closed	Open
3	Open	Open	Open
4	Closed	Open	Open
5	Open	Closed	Open
10	Open	Open	Closed
11	Closed	Open	Closed
12	Open	Closed	Closed
15	Closed	Closed	Closed

ROM ADDRESS SELECTION				
Address	J6	J7	J8	J9
Disabled	Open	Open	Open	Open
C000h	Closed	Open	Open	Open
C400h	Closed	Closed	Open	Open
C800h	Open	Open	Closed	Open
CC00h	Closed	Open	Closed	Open
D000h	Open	Closed	Closed	Open
D400h	Closed	Closed	Closed	Open
D800h	Open	Open	Open	Closed
DC00h	Closed	Open	Open	Closed