

Jumper	Description	On	Off
JP2	Termination Power	Enabled	Disabled

Jumper	Description	On	Off
JP3	HDC IO Address	17X	1FX
JP4	ROM Address	D800	C800

Jumper	Description	On	Off
JP8	Not documented	Enabled	Disabled

Jumper	Description	1-2	2-3
JP10	IRQ Setting	14	15
JP12	IDE Enable/Disable	Enabled	Disabled
JP13	HDC (drive 0) Setting	Yes	No
JP14	LPT Enable/Disable	Enabled	Disabled
JP15	COM 2/4 Selection	COM 2	COM 4
JP16	Floppy Enable/Disable	Enabled	Disabled
JP17	COM 2/4 Enable/Disable	Enabled	Disabled
JP18	LPT2/LPT3 Selection	LPT2	LPT3
JP19	COM 1/3 Selection	COM 1	COM 3
JP20	COM 1/3 Enable/Disable	Enabled	Disabled
JP21	Game Port Enable/Disable	Enabled	Disabled

Connector	Purpose
CN1	COM 1/3
CN2	LPT
CN3	COM 2/4
CN4	Game Port
CN5	IDE LED
CN6	IDE
CN7	Floppy
CN8	50-Pin SCSI
CN9	SCSI LED