

Sound Card



AW200

- Model: [AW200](#)
- Bus Type: [PCI](#)
- Audio Processor: [AS9200 / RealTek ALS4000](#)
- Wavetable Synthesizer: [Software](#)
- Stereo Mixer/Recorder/MIDI Support: [YES/YES/YES](#)
- Internal Modem Connector: [YES](#)

Part NO.	UPC Code.
90.18610.201	7-5051902535-2

Key Features

- AOpen AS9200 / RealTek ALS4000 audio processor
- Compatible with DirectSound® & DirectSound3D®, Sound Blaster™, Sound Blaster Pro™
- PCI 2.1/2.2 Compliant PCI Interface
- PCI Power Management Interface (PPMI) Compliant
- PCI Bus Master for PCI Audio
- Supports DDMA, Advanced Legacy Support for legacy DMAC emulation
- Advanced ALSFM synthesizer
- Analog/Digital Enhanced Gameport
- 3D Effects Processor
- 16-bit full-duplex for concurrent recording and playback

Specifications

- **Audio Chip:**
AOpen AS9200 / RealTek ALS4000 audio processor
3D Effects Processor

Built-in ALSFM synthesizer
Support DirectSound® and DirectSound3D®

- **Record and Playback:**

Record and play back voice, sound and music
16-bit stereo ADC and DAC
Programmable independent sample rate from 8 kHz up to 48 kHz for record and playback
16-bit full-duplex for concurrent recording and playback

- **DOS Legacy Mode Support:**

Support DOS compatible modes: DDMA under Windows 95/98
Sound Blaster™, Sound Blaster Pro™ System compatible

- **I/O Interface:**

MPU-401 UART MIDI I/O Interface
Joystick/Gamepad
Stereo/Line-Out
Mono In/Mono Out/CD Audio/Line-In/
Microphone-In

- **Drivers:**

Support Dos, Windows 95, Windows 98, Windows NT 4.0 & Windows 2000
WDM streaming driver support Windows 98

- **Software:**

Music Center Player
MIDI Board

- **Dimensions:**

120 (L) x 82 (W) x 14.3 (H) mm

A division of Ken-Ding Group

Weizhou International Co., Ltd

P. O. Box 1394 Kaohsiung City, Taiwan ROC

Tel: 886-7-7169249 Fax : 886-7-7169250

e-mail: Weizhou@ms65.hinet.net e-mail : waltershiu@pagic.net