

# MIC-3958 Ethernet Switch Card

## 3U CompactPCI 3 Ports/5 Ports M12 X-Code Ethernet Switch Card



### Features

- IEEE802.3x Support
- Up to 5 Ports robust M12 connectors on front panel
- Auto-negotiation/Auto MDI/MDIX crossover on all ports
- Switch Controller RTL8332M

Fully Compliant with  
**EN 50121-4**

Fully Certified with  
**EN 50155**

**CE FCC**

**RoHS**  
COMPLIANT  
DIRECTIVE

## Introduction

The MIC-3958D is a peripheral board with 3U CPCI former factor and used for Ethernet switch function, it can provide up to 5 ports M12 connectors with auto-negotiation, auto MDI/MDIX crossover switch function. MIC-3958D is designed to meet EN50155 and EN50121-4, with its high capabilities on mechanical, EMC, safety and wide range of environment requirements; it is especially suited for applications in harsh environment like railway and military.

## Specifications

Ethernet Interface	<ul style="list-style-type: none"> <li>▪ 10/100/1000 Base-T via M12 X-Code</li> <li>▪ IEEE802.3x Support</li> </ul>	
Front I/O	<ul style="list-style-type: none"> <li>▪ 3 or 5 ports X-code M12 connectors</li> <li>▪ LED indicators: LNK:Green when connected; ACT: Green Blink when data transferred</li> </ul>	
Rear IO	Reserve 6 x MDI/MDIX to R10	
Dimension	<ul style="list-style-type: none"> <li>▪ 3U/4HP or 8HP, 100x160mm</li> <li>▪ Weight:250g</li> </ul>	
OS support	Windows, Linux	
Power Consumption	Test Environment: windows OS run Passmark burn in 10min <ul style="list-style-type: none"> <li>▪ MIC-3958D1-S1E: 5V/9.7W</li> <li>▪ MIC-3958D1-D1E: 5V/10W</li> </ul>	
Isolation Protection	<ul style="list-style-type: none"> <li>▪ MIC-3958D: 1.2KV AC (ethernet signal to chassis ground)</li> <li>1.5KV AC (ethernet signal to digital ground)</li> </ul> Note: Test <20mA	
Dielectric Withstanding Voltage	<ul style="list-style-type: none"> <li>▪ MIC-3958D: 1.5KV AC, chassis ground to digital ground</li> </ul> Note: Test chassis ground to digital ground, <20mA	
Environment	Temperature	-40 ~ 70 °C (-40 ~ 158 °F)      -40 ~ 85 °C (-40 ~ 185 °F)
	Humidity	10 ~ 95% @ 40 °C, non-condensing      10 ~ 95% @ 60 °C, non-condensing
	Shock	3 G, 30ms, each axis three times
	Vibration	2G rms

## Ordering Information

Product	Product Name	Description
Standard MIC-3958D series <sup>1</sup>	MIC-3958D1-S1E	3U CompactPCI Ethernet Switch Card with 3 ports M12 X-code on 4HP panel
	MIC-3958D1-D1E	3U CompactPCI Ethernet Switch Card with 5 ports M12 X-code on 8HP panel

Note 1: No accessory M12 cable, please contact local sales for cable spec.

## Related Products

CPU board	Description
MIC-3328 Series	3U CompactPCI 3rd generation Ivy bridge Intel® Core™ i3/i7 Processor Blades
MIC-3329 Series	3U CompactPCI Baytrail Intel® Atom™ Low power Processor Blades
MIC-3332 Series	3U CompactPCI 6th generation Skylake Intel® Core™ i7/Xeon E3 Processor Blades

## Products Picture



MIC-3958D1-D1E



MIC-3958D1-S1E