

CLUB AMERICAN TECHNOLOGIES, INC.

EAGLE 300SX SERIES

... continued from previous page

USER CONFIGURABLE SETTINGS		
Function	Jumper	Position
í Factory configured - do not alter	W1	Closed
í Factory configured - do not alter	W2	pins 1 & 2 closed
í Factory configured - do not alter	W3	pins 2 & 3 closed
í On board battery enabled	W4	Closed
On board battery disabled	W4	Open
í Serial port COM1 (J9) at IRQ4	W13	pins 1 & 2 closed
Serial port COM1 (J9) at IRQ3	W13	pins 1 & 3 closed
í Serial port COM2 (J10) at IRQ3	W13	pins 3 & 4 closed
Serial port COM2 (J10) at IRQ4	W13	pins 2 & 4 closed
í Parallel port LPT1 (J12) at IRQ7	W14	pins 2 & 3 closed
Parallel port LPT1 (J12) at IRQ5	W14	pins 1 & 2 closed
í Factory configured - do not alter	W15	Open
í CPU speed select switchable from keyboard	W16	pins 1 & 2 closed
CPU speed select slow	W16	pins 2 & 3 closed
í Monitor type select color	W17	Closed
Monitor type select monochrome	W17	Open
í Factory configured - do not alter	W18	Closed

DRAM CONFIGURATION				
Size	Bank 0	Bank 1	Bank 2	Bank 3
512KB	(2) 256K x 9	NONE	NONE	NONE
1MB	(2) 256K x 9	(2) 256K x 9	NONE	NONE
1.5MB	(2) 256K x 9	(2) 256K x 9	(2) 256K x 9	NONE
2MB	(2) 256K x 9			
2MB	(2) 1M x 9	NONE	NONE	NONE
2.5MB	(2) 256K x 9	(2) 1M x 9	NONE	NONE
3MB	(2) 256K x 9	(2) 256K x 9	(2) 1M x 9	NONE
4MB	(2) 1MB x 9	(2) 1M x 9	NONE	NONE
4.5MB	(2) 1M x 9	(2) 1M x 9	(2) 256K x 9	NONE
5MB	(2) 256K x 9	(2) 256K x 9	(2) 1M x 9	(2) 1M x 9
6MB	(2) 1M x 9	(2) 1M x 9	(2) 1M x 9	NONE
8MB	(2) 1M x 9			
8MB	(2) 4M x 9	NONE	NONE	NONE
8.5MB	(2) 256K x 9	(2) 4M x 9	NONE	NONE
9MB	(2) 256K x 9	(2) 256K x 9	(2) 4M x 9	NONE
10MB	(2) 1M x 9	(2) 4M x 9	NONE	NONE
12MB	(2) 1M x 9	(2) 1M x 9	(2) 4M x 9	NONE
16MB	(2) 4M x 9	(2) 4M x 9	NONE	NONE