

KOUWELL ELECTRONIC CORPORATION

KW - 330

... continued from previous page

| USER CONFIGURABLE SETTINGS | | |
|--------------------------------|--------|----------|
| Function | Jumper | Position |
| Monitor type select color | JP5 | Closed |
| Monitor type select monochrome | JP5 | Open |

| DRAM CONFIGURATION | | | | | | |
|--------------------|-------------|------------|--------------|------------|--------------|--------------|
| Size | Bank 0(DIP) | P-0 | Bank 1 (DIP) | P-1 | Bank 2 (SIP) | Bank 3 (SIP) |
| 512KB | (4) 44256 | (2) 41256 | NONE | NONE | NONE | NONE |
| 1MB | (4) 44256 | (2) 41256 | (4) 44256 | (2) 41256 | NONE | NONE |
| 1.5MB | (4) 44256 | (2) 41256 | (4) 44256 | (2) 41256 | (2) 256K x 9 | NONE |
| 2MB | (4) 44256 | (2) 41256 | (4) 44256 | (2) 41256 | (2) 256K x 9 | (2) 256K x 9 |
| 2MB | (16) 411000 | (2) 411000 | NONE | NONE | NONE | NONE |
| 4MB | (16) 411000 | (2) 411000 | (16) 411000 | (2) 411000 | NONE | NONE |
| 6MB | (16) 411000 | (2) 411000 | (16) 411000 | (2) 411000 | (2) 1M x 9 | NONE |
| 8MB | (16) 411000 | (2) 411000 | (16) 411000 | (2) 411000 | (2) 1M x 9 | (2) 1M x 9 |

| DRAM WAIT STATE CONFIGURATION | | |
|-------------------------------|-------------------|-------------------|
| Wait states | JP1 | JP2 |
| 0 | pins 1 & 2 closed | pins 1 & 2 closed |
| 1 | pins 1 & 2 closed | pins 2 & 3 closed |

| BIOS CONFIGURATION | | |
|--------------------|-------------------|-------------------|
| Size | JP3 | JP4 |
| 27256 | pins 2 & 3 closed | pins 1 & 2 closed |
| 27512 | pins 1 & 2 closed | pins 2 & 3 closed |