


ASUS COMPUTER INTERNATIONAL ISA - 486

Processor 80486SX/80487SX/80486DX
Processor Speed 16/20/25/33/50MHz
Chip Set SIS
Max. Onboard DRAM 64MB
Cache 64/128/256KB
BIOS AMI
Dimensions 330mm x 218mm
I/O Options 32-bit memory card
NPU Options 4167



| CONNECTIONS | | | |
|--------------|----------|------------------------------|----------|
| Purpose | Location | Purpose | Location |
| Reset switch | CN1 | Keylock & power LED | CN5 |
| Turbo switch | CN2 | External battery | CN6 |
| Turbo LED | CN3 | 32-bit memory expansion slot | S1 |
| Speaker | CN4 | | |

Continued on next page...

ASUS COMPUTER INTERNATIONAL

ISA - 486

...continued from previous page

| USER CONFIGURABLE SETTINGS | | |
|--|--------|-------------------|
| Function | Jumper | Position |
| i Power good signal detect from power supply | JP1 | pins 1 & 2 closed |
| Power good signal detect from board | JP1 | pins 2 & 3 closed |

| CPU TYPE | | | | | | |
|----------|-------|-------|-------|-------|-------|-------|
| Type | SW1/1 | SW1/2 | SW1/3 | SW1/4 | SW1/5 | SW1/6 |
| 80487SX | Off | On | On | On | Off | On |
| 80486SX | Off | Off | Off | Off | On | On |
| 80486DX | On | On | On | Off | Off | Off |

| CLOCK SPEED SELECT | | |
|--------------------|-------------------|-------------------|
| Speed | JP2 | JP3 |
| 16MHz | pins 2 & 3 closed | pins 2 & 3 closed |
| 20MHz | pins 2 & 3 closed | pins 2 & 3 closed |
| 25MHz | pins 2 & 3 closed | pins 1 & 2 closed |
| 33MHz | pins 2 & 3 closed | pins 1 & 2 closed |
| 50MHz | pins 1 & 2 closed | pins 1 & 2 closed |

| CACHE CONFIGURATION | | |
|---------------------|-------------|-------------|
| Size | Bank 0 | Bank 1 |
| 64KB | (4) 8K x 8 | (4) 8K x 8 |
| 128KB | (4) 32K x 8 | NONE |
| 256KB | (4) 32K x 8 | (4) 32K x 8 |

| CACHE RESISTOR CONFIGURATION | | | |
|------------------------------|---------------|---------------|---------------|
| Size | CJ1 | CJ2 | CJ3 |
| 64KB | Installed | Not installed | Not installed |
| 128KB | Not installed | Installed | Not installed |
| 256KB | Not installed | Not installed | Installed |

Continued on next page...

ASUS COMPUTER INTERNATIONAL ISA - 486

...continued from previous page

| DRAM CONFIGURATION | | | | |
|--------------------|--------------|--------------|------------|------------|
| Size | Bank 0 | Bank 1 | Bank 2 | Bank 3 |
| 1MB | (4) 256K x 9 | NONE | NONE | NONE |
| 2MB | (4) 256K x 9 | (4) 256K x 9 | NONE | NONE |
| 4MB | (4) 1M x 9 | NONE | NONE | NONE |
| 6MB | (4) 256K x 9 | (4) 256K x 9 | (4) 1M x 9 | NONE |
| 8MB | (4) 1M x 9 | (4) 1M x 9 | NONE | NONE |
| 10MB | (4) 256K x 9 | (4) 256K x 9 | (4) 1M x 9 | (4) 1M x 9 |
| 12MB | (4) 1M x 9 | (4) 1M x 9 | (4) 1M x 9 | NONE |
| 16MB | (4) 1M x 9 | (4) 1M x 9 | (4) 1M x 9 | (4) 1M x 9 |
| 16MB | (4) 4M x 9 | NONE | NONE | NONE |
| 18MB | (4) 256K x 9 | (4) 256K x 9 | (4) 4M x 9 | NONE |
| 20MB | (4) 256K x 9 | (4) 4M x 9 | NONE | NONE |
| 24MB | (4) 1M x 9 | (4) 1M x 9 | (4) 4M x 9 | NONE |
| 32MB | (4) 4M x 9 | (4) 4M x 9 | NONE | NONE |
| 36MB | (4) 1M x 9 | (4) 4M x 9 | (4) 4M x 9 | NONE |
| 40MB | (4) 1M x 9 | (4) 1M x 9 | (4) 4M x 9 | (4) 4M x 9 |
| 48MB | (4) 4M x 9 | (4) 4M x 9 | (4) 4M x 9 | NONE |
| 64MB | (4) 4M x 9 | (4) 4M x 9 | (4) 4M x 9 | (4) 4M x 9 |

OPTIONAL 32-BIT MEMORY CARD

