


# EURONE

## EM-5598SG

<b>Device Type</b>	Mainboard
<b>Processor</b>	CX 6X86L/IBM 6X86L/CX 6X86MX/IBM 6X86MX/CX M2/AM K6/AM K6-2/Pentium/Pentium MMX/IDT C6
<b>Processor Speed</b>	90/100/150/166/200/225/233/240/266/300/333/350/366/380/400/450/475MHz
<b>Chip Set</b>	SIS 530
<b>Video Chip Set</b>	Unidentified
<b>Audio Chip Set</b>	Unidentified
<b>Maximum Onboard Memory</b>	768MB (SDRAM supported)
<b>Maximum Video Memory</b>	8MB (shared from system memory)
<b>Maximum Audio Memory</b>	Unidentified
<b>Cache</b>	1024/2048KB
<b>BIOS</b>	Unidentified
<b>Dimensions</b>	220mm x 220mm
<b>I/O Options</b>	32-bit PCI slots (3), floppy drive interface, game/MIDI interface, IDE interfaces (2), parallel port, PS/2 mouse interface, serial interfaces (2), VGA feature connector, IR interface, USB interfaces (2), ATX power connector, line in, line out, microphone in, audio in - CD-ROMs (2), Wake-on-LAN connector



CONNECTIONS			
Purpose	Location	Purpose	Location
ATX power connector	ATX	Turbo LED	J2/Pins 13 & 14
IDE interface 2	CN1	IDE interface LED	J2/Pins 15 & 16

IDE interface 1	CN2	Reset switch	J2/Pins 17 & 18
VGA feature connector	CN3	Power supply	J2/Pins 21 & 22
Parallel interface	CN4	Audio in - CD-ROM (Sony)	J4
Serial interface 2	CN5	Audio in - CD-ROM (Panasonic)	J5
Serial interface 1	CN6	Sound & game/MIDI interface	J7
Floppy drive interface	CN8	Digital audio interface	J8
CPU fan power	FAN1	SPDIF in	J9
IR connector 1	IR1	PS/2 mouse interface	J10
ATX form card connector	J1	Wake-on-LAN connector	JP1
Speaker	J2/Pins 1, 3, 5, 7	32-bit PCI slots	PC1-PC3
Power LED & keylock	J2/Pins 2, 4, 6, 8, 10		

### USER CONFIGURABLE SETTINGS

Function		Label	Position
»	SPDIF out signal voltage selection 5v	J6	Closed
	SPDIF out signal voltage selection 0.5v	J6	Open
»	Keyboard power on disabled	JP2	Pins 1 & 2 closed
	Keyboard power on enabled	JP2	Pins 2 & 3 closed
»	CMOS memory normal operation	JP3	Pins 1 & 2 closed
	CMOS memory clear	JP3	Pins 2 & 3 closed

### DIMM CONFIGURATION

Size	Bank 0	Bank 1	Bank 2
4MB	(1) 512KB x 64	None	None
8MB	(1) 1M x 64	None	None
8MB	(1) 512KB x 64	(1) 512KB x 64	None
12MB	(1) 512KB x 64		(1) 512KB x 64

		(1) 512KB x 64	
16MB	(1) 2M x 64	None	None
16MB	(1) 1M x 64	(1) 1M x 64	None
20MB	(1) 1M x 64	(1) 1M x 64	(1) 512KB x 64
24MB	(1) 1M x 64	(1) 1M x 64	(1) 1M x 64
32MB	(1) 4M x 64	None	None
32MB	(1) 2M x 64	(1) 2M x 64	None
36MB	(1) 2M x 64	(1) 2M x 64	(1) 512KB x 64
40MB	(1) 2M x 64	(1) 2M x 64	(1) 1M x 64
48MB	(1) 2M x 64	(1) 2M x 64	(1) 2M x 64
64MB	(1) 8M x 64	None	None
64MB	(1) 4M x 64	(1) 4M x 64	None
68MB	(1) 4M x 64	(1) 4M x 64	(1) 512KB x 64
72MB	(1) 4M x 64	(1) 4M x 64	(1) 1M x 64
80MB	(1) 4M x 64	(1) 4M x 64	(1) 2M x 64
96MB	(1) 4M x 64	(1) 4M x 64	(1) 4M x 64
128MB	(1) 16M x 64	None	None
128MB	(1) 8M x 64	(1) 8M x 64	None
132MB	(1) 8M x 64	(1) 8M x 64	(1) 512KB x 64
136MB	(1) 8M x 64	(1) 8M x 64	(1) 1M x 64
144MB	(1) 8M x 64	(1) 8M x 64	(1) 2M x 64
160MB	(1) 8M x 64	(1) 8M x 64	(1) 4M x 64
192MB	(1) 8M x 64	(1) 8M x 64	(1) 8M x 64
256MB	(1) 16M x 64	(1) 16M x 64	None
256MB	(1) 32M x 64	None	None
260MB	(1) 16M x 64	(1) 16M x 64	(1) 512KB x 64
264MB	(1) 16M x 64	(1) 16M x 64	(1) 1M x 64
272MB	(1) 16M x 64	(1) 16M x 64	(1) 2M x 64
288MB	(1) 16M x 64	(1) 16M x 64	(1) 4M x 64

288MB	(1) 16M x 64	(1) 16M x 64	(1) 4M x 64
320MB	(1) 16M x 64	(1) 16M x 64	(1) 8M x 64
384MB	(1) 16M x 64	(1) 16M x 64	(1) 16M x 64
512MB	(1) 32M x 64	(1) 32M x 64	None
516MB	(1) 32M x 64	(1) 32M x 64	(1) 512KB x 64
520MB	(1) 32M x 64	(1) 32M x 64	(1) 1M x 64
528MB	(1) 32M x 64	(1) 32M x 64	(1) 2M x 64
544MB	(1) 32M x 64	(1) 32M x 64	(1) 4M x 64
576MB	(1) 32M x 64	(1) 32M x 64	(1) 8M x 64
640MB	(1) 32M x 64	(1) 32M x 64	(1) 16M x 64
768MB	(1) 32M x 64	(1) 32M x 64	(1) 32M x 64

Note: Board supports SDRAM memory.