

IP-4GVI83

Socket 478 ATX Board for Pentium® 4 / Celeron™ Processor with VGA / LAN / Audio

Key-point:

- > Socket 478 for Intel® Pentium® 4 / Celeron™ Processor, up to 3.06GHz
- > Intel® 845GV Chipsets, 400 / 533 MHz FSB
- > Chipset integrated VGA function
- > Intel® 82562ET Ethernet, Support 10/100 Base-TX Ethernet
- > AC97 Audio, 6 x USB 2.0 ports / 2 x COM ports
- > 1 x AGP slot for ADD card / 4 x PCI / 3 x ISA Slots
- > WatchDog Timer & Hardware monitoring function



Specifications:

- ⊙ **Processor:**
 - * Support Intel® Socket 478 Pentium® 4 / Northwood™ / Celeron™ Processor, Up to 3.06GHz
- ⊙ **Core Logic:**
 - * Intel® 845GV + ICH4 chipsets
- ⊙ **BIOS:**
 - * Award BIOS
- ⊙ **Front Side Bus Speed:**
 - * 400 / 533 MHz
- ⊙ **Memory:**
 - * Two 184-pins DIMM support 2GB DDR266/333 SDRAM (max.)
- ⊙ **Onboard VGA Controller:**
 - * Intel® 845GV chipset integrated VGA function,
 - * AGP slot for ADD card only
- ⊙ **LAN Controller:**
 - * Intel® 82562ET, for 10/100 Base-TX Ethernet
- ⊙ **Onboard IDE:**
 - * Two EIDE channels for PIO Mode, DMA Mode
 - * Supports four ATA 100/66/33 IDE devices
- ⊙ **Multi I/O:**
 - Onboard Winbond® W83627HF chip, Support:
 - * 1 x IrDA by 5-pin pin-header,
 - * 1 x Floppy Interface
 - * 1 x SPP / EPP / ECP parallel port
 - * 2 x COM ports for RS-232
- ⊙ **Keyboard / Mouse Connector:**
 - * Staked connector for PS/2 type keyboard / mouse
 - * 1 x 6-pins connector for external keyboard / mouse
- ⊙ **USB:**
 - * Support 6 x USB 2.0 ports, Four USB ports on rear panel
 - * 2 x USB ports by pin-headers, Optional USB cable with bracket
- ⊙ **Audio:**
 - * AC97 Audio codec
- ⊙ **WatchDog Timer:**
 - * 256 Levels software programmable
- ⊙ **Hardware Monitoring:**
 - * Winbond® W83627HF chip, Monitoring for CPU and system temperature, voltage and fan speed
- ⊙ **Extension slot:**
 - * 1 x AGP slot for ADD card only
 - * 4 x PCI slots
 - * 3 x ISA slots
- ⊙ **Environments:**
 - * Operation temperature: 0°C to 60°C (32° F to 140° F)
 - * Storage temperature: -20°C to 80°C (-68° F to 176° F)
 - * Relative humidity: 10% to 90% (Non-Condensing)
- ⊙ **Certification:**
 - * CE, FCC Approval
- ⊙ **Others features**
 - * 3 x fan connectors
- ⊙ **Form Factor:**
 - * ATX form factor 12" x 8.7" (305mm x 220mm)

*Specification is subject to change without prior notice

Ordering Information:

Model No.	Position	Support LCD	Support VGA	Support Audio	Support LAN	Support AGP/PCI /ISA
IP-4GVI83	Standard Product	---	Yes	Yes	Yes	1(for ADD Card) / 4 / 3

I/O Shield Layout

