


Socket 370



SST-5771

INTEL 440ZX ATX MOTHERBOARD



SPECIFICATION : -



DMI COMPLY



Software Bundle



Processor	- Intel® Pentium® III & Celeron® (66/100Mhz Front Side Bus) (PGA 370 Type). - 300/333/350/366/400/433/450/466/500/533/550/600/650/667/700MHz or above.
Chip Set	- Intel® 440ZX
BIOS	- 2M Flash EPROM (Support PnP, APM, ACPI, ATAPI, DMI). - IDE AUTO LBA Mode Supports HDDs over 8.4GB. - Trend Micro ChipAway Virus Protection.
Cache	- L2 Cache is CPU Built-in.
Memory	- Size up to 256MB - Two 168-pins DIMMs - DIMMs Depth of 1MB, 2MB, 4MB, 8MB, 16MB and 32MB.
On Board I/O	- Support Two PCI Enhanced IDEs PIO Mode 3, Mode 4 and Ultra DMA 33 Channels. - Twin Headers for Four IDE Devices Including IDE HDDs and CD ROMs. - Support Two FDDs of 360KB, 720KB, 1.2MB, 1.44MB or 2.88MB. - One ECP/EPP Parallel Port, Two 16550A UART Serial Ports, Two USB Ports, PS/2 Mouse Port, PS/2 Keyboard Port,
On Board Sound	- Creative ES1373 PCI Sound Chip. - PnP, Creative 3D Enhancement, Wave Synth Wave Table. - Full-Duplex, Sound Blaster 16 Compatible. - Line-in, Line-out, Mic-in and MIDI/Game Port.
Expansion Slot	- Two ISA Bus Slots (One PCI Shared Slot). - Four PCI Bus Slots - One Accelerated Graphics Port (AGP).
Plug and Play	- Plug and Play Specification 1.1. - Plug and Play for DOS®, Windows® 3.x, and Windows® 95.
PC97/98	- PC97/98 Ready, PC99 Color Connector.
Power Management	- Support SMM, APM and ACPI. - Comply to Energy Star "Green PC" Program. - Supports WAKE-ON-LAN (WOL). - Supports Modem Ring-in Wake Up.
PCI	- PCI 2.1.
AGP	- AGP 1.0.
VRM	- On Board VRM 8.4.
Battery	- On-board Lithium Battery.
Others	- CPU Frequency Multiplier Jumperless (optional). - Alarm Wake-up. - Bundle "PC-cillin 6" Anti Virus Software
Board Size	- 173mm x 305mm, ATX Form Factor.