


Socket 7

ASKA®

SST-5852

VIA APOLLO MVP4 BABY AT MOTHERBOARD



SPECIFICATION : -

Processor	<ul style="list-style-type: none">- Intel® Pentium®, Cyrix®6x86/6x86L/6x86MX/III, AMD® K5/K6/K6-3, IBM® 6x86/6x86L/6x86MX, IDT WinChip C6 (66, 75, 83, 100MHz Front Side Bus).- 166/180/200/233/266/300/350/400/450/500MHz or above.- Intel® Pentium® Processors with MMX™Technology.- Socket 7 CPU Upgradability.
Chip Set	<ul style="list-style-type: none">- VIA® APOLLO MVP4
BIOS	<ul style="list-style-type: none">- 2MB Flash EPROM (Support PnP, APM, ATAPI & Windows® 95).- IDE AUTO LBA Mode Supports HDDs over 8.4GB.- Anti-Virus Protection.
External Cache	<ul style="list-style-type: none">- Direct Mapped L2 Write Back Cache.
Memory	<ul style="list-style-type: none">- 512KB On-board Synchronous Pipelined Burst SRAM.- 8MB to 256MB.- Two 168-pins DIMMs (64bit) Synchronous DRAM (SDRAM).- DIMMs Depth of 1MB, 2MB, 4MB, 8MB and 16MB.
On Chip AGP	<ul style="list-style-type: none">- AGP v1.0 Compliant.- Transfer Rate up to 533MB/sec.- 64-bit Single Cycle 2D/3D Graphic Engine.- Support 2 to 8MB Frame Buffer Shared with System Memory.- Integrated 24-bit 230MHz RAM DAC.- Resolution up to 1600 x 1200.- DirectX 6 & OpenGL API.- Win95 VXD, Win98/NT5 Minport Driver Support.
On Board I/O	<ul style="list-style-type: none">- Support Two PCI Enhanced IDEs PIO Mode 3, Mode 4 and Ultra DMA 33/66 Channels (Optional Ultra DMA 66 Cable). Twin Headers for Four IDE Devices Including IDE HDDs and CDROMs.- Support Two FDDs of 360KB, 720KB, 1.2MB, 1.44MB or 2.88MB.- One ECP/EPP Parallel Port. Two 16550A UART Serial Ports. Two USB Ports (Optional Adapter Cable). One PS/2 Mouse Port (Optional Adapter Cable). One IrDA Port (Optional TX/RX Module).
On Board Sound	<ul style="list-style-type: none">- On Chip AC97 Audio Controller with Standard AC97 Codec.- PnP, Full-Duplex, Sound Blaster Pro, Direct Sound Ready.- Line-in, Line-out, Mic-in and MIDI/Game Port (via Cable).
Expansion Slot Plug and Play	<ul style="list-style-type: none">- One ISA Bus Slots, Three PCI Bus Slots, One Audio Modem Riser (AMR).- Plug and Play Specification 1.1.- Plug and Play for DOS®, Windows® 3.x, and Windows® 95.
PC97/98 Power Management	<ul style="list-style-type: none">- PC97/98 Ready PC99 Color Connector.- Support SMM & APM.- Comply to Energy Star "Green PC" Program.
PCI Others	<ul style="list-style-type: none">- PCI 2.1 Compliant.- On-board Lithium Battery.- Bundle "PC-cillin 6" Anti Virus Software
Board Size	<ul style="list-style-type: none">- 220mm x 186mm, Baby AT Form Factor.



DMI COMPLY



Software Bundle

