


**Socket 478
(Pentium 4)**

**ASKA® SST-6840ACD
INTEL® 865PE DDR ATX MOTHERBOARD**



SPECIFICATION : -

Processor	- Intel® Pentium® 4/5(Prescott) (478pin package) (533/800MHz FSB).
Chip Set	- Intel® 865PE+ ICH5
BIOS	- Firmware Hub. - Support PnP, APM, ACPI, ATAPI, DMI. - Trend Micro ChipAway Virus Protection.
Cache	- L2 Cache is CPU Built-in.
Memory	- Four DDR Sockets Supports Dual Channel DDR 400 up to 2GB.
On Board I/O	- Support Two Serial ATA-150 Ports on board. - Support Two PCI Enhanced IDEs PIO Mode 3, Mode 4 and Ultra DMA 33/66/100 Channels. Twin Headers for Four IDE Devices Including IDE HDDs and CDROMs. - Support Two FDDs of 360KB, 720KB, 1.2MB, 1.44MB or 2.88MB. - One ECP/EPP Parallel Port, Two 16550A UART Serial Ports, Eight USB 2.0 Ports (Six USB Ports by Optional Adapter Cable), PS/2 Mouse Port, PS/2 Keyboard Port, Integrated AC97 Controller with Standard AC97 Codec.
On Board Sound	- PnP, Full-Duplex, Sound Blaster and Direct Sound Ready. - Line-in, Line-out, Mic-in and MIDI/Game Port . - Optional 6 Channel Audio Codec Support.
On Board Lan (Optional)	- 10/100 Mb/s Lan (RT8100B).
1394 (Optional)	- Two Ports of IEEE1394 on board.
Expansion Slot	- Six PCI Bus Slots. - One Accelerated Graphics Port (AGP 8X support).
Plug and Play	- Plug and Play Specification 1.1. - Plug and Play for DOS®, Windows® 3.x, and Windows® 95/98/2000/XP.
PC97/98	- PC97/98 Ready, PC99 Color Connector.
Power Management	- Support SMM, APM and ACPI. - Comply to Energy Star "Green PC" Program. - Supports WAKE-ON-LAN (WOL). - Supports Modem Ring-in Wake Up.
AGP	- AGP 3.0.
VRD	- On Board VRD10.
Battery	- On-board Lithium Battery.
Others	- Alarm Wake-up. - Bundle "PC-cillin" Anti Virus Software.
Board Size	- 228mm x 305mm, ATX Form Factor.



DMI COMPLY



Software Bundle

