



AcerAltos 920 - Extended Specifications

Processor	Intel Pentium II, 233 MHz with 512 KB ECC cache memory integrated into the processor
Internal memory	32 MB EDO DIMM, expandable to 512 MB
Expansion Slots	A total of seven expansion slots: five 32-bit PCI slots and two 16-bit ISA slots
Storage Controller	Two integrated Ultra & Wide SCSI controllers with two 68-pin outputs and one 50-pin output
Storage options	Four hard drive bays, max storage capacity, 36.4 GB (4 x 9.1 GB)
Floppy disc drive	3.5" floppy drive, 1.44 MB
External Connections	One mouse connector, one keyboard connector, one parallel connector, two serial connectors, one RJ-45 connector, one USB connector
Display control	Integrated graphics controller, max Resolution 1,024 x 768 at 256 colours 1 MB video memory expandable to 2 MB
Power	250 Watt power supply
Security	Case Lock, Startup password, Setup password, Floppy disk boot control, Floppy disk drive control, Fixed disk drive control, Serial Interface Control, Parallel Interface Control, Reset control
Server Management Capabilities	Acer Advanced Server Manager: Preventive maintenance and fault detection, heat generation server, status cooling fans and power supply, ECC memory, network interface Performance registration: I/O bus, network interface, optimization disk volume, ECC memory and the processor Management: general system status, configuration settings, alarm notifications in case of error messages Acer Remote Diagnostic Module, Remote system management via a modem Start-up management, including POST notifications Remote Console Facilities
Supported Operating Systems	Novell IntranetWare, Novell NetWare 3.12 and 4.1x, Novell NetWare SFT III 4.11, Novell NetWare SMP 4.11, SCO Openserver release 5, Microsoft Windows NT 3.51, 4.0, Microsoft Windows 95, IBM OS/2, MS-DOS 5 and 6.
Software	DOS 62 is installed on the models that are equipped with a hard disk as standard Acer Advanced Server Manager, Agent and Client, Acer Remote Diagnostic Management, Acer Easy Build
Dimensions	441 mm (h) x 208 mm (b) x 520 mm (d)
Guarantee	Three years on labour and parts and the first year including free call-out service
Options	
Processor	Second Intel Pentium II processor.
Memory Expansion	16 MB, 32 MB, 64 MB, and 128 MB EDO ECC DIMM (Dual Inline Memory Module) memory modules
Storage options	2GB, 4GB, and 9GB plugable hard drives, 3.5 floppy drive, SCSI CD-ROM
Back-up	8 GB internal DAT recorder DDS-2
SCSI Cable & Connector	Cable for 4 Ultra & Wide units and an external connection (68-pin)
	cable for 2 Ultra & Wide units and an external connection
Monitors	15" and 17" colour displays
UPS	Smart-UPS 450VA, Smart-UPS 1000VA, incl. PowerChute Plus with NT, WFW, Windows 95 and Novell PowerChute Plus with SCO

