

## AMD K6-2 450~550 MHZ CPU setting table

( with PC-100 SDRAM combination, if early PC-66 SDRAM , please follow Async setting BIOS ver : 1.0 08 )

### 1. Voltage setting

Voltage	SW2			
	1-5	2-6	3	4
2.2 V	Off	On	Off	Off
2.3 V	On	On	Off	Off
2.4 V	Off	Off	On	Off

### 2. Frequency setting

Frequency	SW1						JP2
	1	2	3	4	5	6	
<b>K6-2 &amp; III 450</b>	Off	Off	On	On	On	On	1-2
<b>K6-2+ 450</b>	Off	Off	On	On	On	On	1-2
<b>K6-2 475</b>	On	Off	On	Off	On	On	1-2
<b>K6-2 500</b>	Off	Off	On	Off	On	On	1-2
<b>K6-2 550</b>	Off	Off	On	Off	Off	On	1-2

### 3. other common setting :

**JP1 : 1-3 , 2-4 close**

**JP3 : 2-3 close**

**JP4 : 1-2 close**

### \*\*\* Recommendation :

1. Do not plug too High-End AGP ( TNT series , Voodoo 3 ) card .  
suggestion as below 8MB , such as : SiS 6326 , S3 Trio3D , Trident 9850 display cards .
2. Shall use “ Bigger “ CPU FAN for high speed CPU .

### 1. AMD K6-2 450 MHZ ( 100 x 4.5 2.3V )