


# Server Board BF55X

**Arima**  
Server



Model	Infini-band
BF553	x
BF557	SDR
BF558	DDR

## Benefits:

- BF55x provides excellent computing performance by 2 Intel Dual/Quad Core Xeon CPU for HPC Marketing

- Get highest performance by Infiniband for Storage Marketing

- Arima's server management solution improves the manageability of enterprise IT systems, lower total cost of ownership and prevent system downtime.

## Specification:

### Processors

- Dual LGA-771 Socket
- Supports Intel Dempesey, Woodcree, Clovotown Series CPU

### Chipset

- Intel Blackford MCH + ESB2
- Winbond Super I/O NS87427
- Mellanox MT25208 Series Infiniband controller

### Memory

- 16\* Memory Slot
- Supports DDR2 667/553 FBDIMM Memory up to 64GB

### BIOS

- 8Mb Flash EEPROM with Phoenix BIOS

### IDE

- Supports UDMA100/66/33 IDE drives and ATAPI compliant devices

### VGA

- XGI Z9s with 32MB DDR2 RAM

### SATA2

- 6\* SATAII Ports (via ESB2)
- Supports Intel RAID for 0,1,10 and JBOD

### LAN

- Intel 82563 Dual port GbE PHY
- 2\* RJ45 GbE connector

### Expansion Slots

- 1\* PCI-E x16 slot (x8 Signal)
- 1\* PCI-E x8 slot
- 1\* PCI-E x4 slot
- 1\* PCI-X slot

### Server Management

- OPMA socket
- Monitors CPU temperature/voltages, FAN status, +3.3V, +5V, ±12V & +5V standby

### Integrated I/O Interface

- 1\* Slim Type Floppy connector
- 6\* USB 2.0 ports (2Rear, 4Front panel header)
- 2\* (9-pin) serial ports with UART 16550 (1Rear, 1Front panel header)
- 2\* PS/2 ports for Keyboard and Mouse
- 1\* DB-15 VGA connector
- 3\* RJ-45 LAN ports (1 10M/100M dedicated for OPMA)

### Form Factor

- SSI EEB form factor, size: 12" X 13"
- 10 Layers
- EPS 12V power connectors (24pin + 8pin + 4Pin)

Option Parts	Description
OPMA Card	Arima Scorpio2 Card
OPMA Card	Arima Aquarius Card

## Arima Computer Corporation

No.758, Sec.4, Bade Road, Taipei 10567, Taiwan  
Tel: 886-2-27495588 Fax: 886-2-27618010

E-mail: server\_usa@arima.com.tw, server\_europe@arima.com.tw, server\_japan@arima.com.tw, server\_asia@arima.com.tw,