

BIOS Revision History

Gigabyte GA-5AX	
BIOS Version (Date)	Version Description
F4 (Aug.23, 2001)	<ol style="list-style-type: none"> 1. For PCB 3.0, 4.1, and 5.x. 2. Support AMD K6-3+ CPU 3. Supports 64G HDD 4. Includes AWDFLASH.EXE
F3 (Dec.15, 1999)	<ol style="list-style-type: none"> 1. For PCB 3.0, 4.1, and 5.x. 2. Support Windows 2000 ACPI mode installation. 3. Set default value of "CPU Write Allocation" to enable. 4. Includes AWDFLASH.EXE
F2 (Oct.21, 1999)	<ol style="list-style-type: none"> 1. For PCB 3.0, 4.1, and 5.x. 2. Support IR function(PCB 5.x). 3. Support UDMA 66(PCB 5.x). 4. Includes AWDFLASH.EXE
F1 (Oct.07, 1999)	<ol style="list-style-type: none"> 1. For Rev.3 & Rev.4 2. Fix the system waken up by RTC in ACPI mode 3. Includes AWDFLASH.EXE
1.5 (Jun.25, 1999)	<ol style="list-style-type: none"> 1. For Rev.3 & Rev.4 2. Fixed Strees test in HCT8.2 failed on W2K build:2031 ACPI 3. Includes AWDFLASH.EXE
1.3 (Dec.30, 1998)	<ol style="list-style-type: none"> 1. For Rev.3 & Rev.4 2. Fixed system hang when detecting HDD 3. Includes AWDFLASH.EXE
1.2 (Nov.19, 1998)	<ol style="list-style-type: none"> 1. Release version. (for PCB 4.1) 2. Includes AWDFLASH.EXE
1.10 (Nov.23, 1998)	<ol style="list-style-type: none"> 1. Support K6-2 380/400(CXT) CPU 2. Includes AWDFLASH.EXE
1.08 (Jul.20, 1998)	<ol style="list-style-type: none"> 1. Add "Auto Detect DIMM/PCI Clk" item 2. Add "Spread Spectrum" item 3. Add "POWER ON/OFF Function" item
1.07 (Jun.19, 1998)	<ol style="list-style-type: none"> 1. Add NCR SCSI BIOS ROM
1.06 (Jun.15, 1998)	<ol style="list-style-type: none"> 1. Add Wake On LAN support
1.05 (Jun.15, 1998)	<ol style="list-style-type: none"> 1. Fixed easy hang at 0b for Ali + ET6000 + AHA 2940W 2. Remove "Susp, stby-> off" Item under video off option of Power Management
1.04 (Jun.15, 1998)	<ol style="list-style-type: none"> 1. Initial release