



EM-9560

5.25" Intel ULV Celeron EBC with Onboard Memory/VGA/LCD/Audio/LAN/USB 2.0/CF/DOC



FEATURES

- Intel ULV Celeron 400MHz Fan-less or 650MHz CPU
- Onboard 128MB SDRAM system memory
- Supports 36-bit TFT LCD and 2 channels 18-bit LVDS LCD
- Type I/II CompactFlash socket and M-system DiskOnChip 2000
- 4 x USB 2.0 ports and 4 COMs / 1 Parallel / 1 IrDA
- PC/104 and PC/104+ expansion bus




FEATURE	DESCRIPTION		
Platform	Form Factor	5.25" EBC	
	Processor	Onboard Intel ULV Celeron 400MHz Fanless or 650MHz	
	Chipset	VIA VT8606 / VT82C686B	
	BIOS	Award Flash BIOS	
	Cache Memory	Processor Built-in	
System Memory	Technology	SDRAM	
	Onboard	128MB (16Mbx16 with 4chips)	
	Max Capacity	512MB	
	Socket	144-pin SO-DIMM x1	
	Storage Interface	IDE Interface	IDE x2
SSD (CF Socket)		CompactFlash /II x1	
DOC		DOC socket x1, supports M-system DiskonChip 2000 Flash memory module	
Networking	Speed	10/100 Mbps	
	I/O	RJ45 x 1	
	Controller	Realtek TRL8139C+	
Display	Controller	VIA VT8606 integrated S3 Savage 4 2D/3D Video Accelerator	
	Output	CRT ,LCD ,Dual LVDS	
Audio	Codec	AC'97 codec	
	I/O	Mic-in, Line-in, Line-out	
I/O Interface	Floppy Drive Interface	FDD header x 1	
	Serial Port	RS-232 x3, RS-232/422/485 x1	
	Parallel Port	1	
	Universal Serial Bus	4 (v2.0)	
	Digital I/O	8-bit input, 8-bit output	
	Bus interface	PC/104, PCI104+	
	IR Interface	115k bps, IrDA 1.0 compliant	
	Keyboard	PS/2	
	Mouse	Shared with keyboard connector	
	Hardware Monitoring	Controller	Winbond W83977EF intergated Hardware monitor funciton
		RTC	Winbond W83977EF integrated RTC within Li-Battery
Watchdog timer		256-level time-out intervals	
Cooling	Heatsink & Fan		
Expansion	PC/104 x1; PC/104+ x1		
Environmental Parameters	Temperature, ambient operating	0~60°C (32~140°F)	
	Humidity (RH), ambient operating	5~95% relative humidity, non-condensing	
	Storage Temperature	-20~70°C (-4~158°F)	
Physical Dimensions	Dimensions	203 x 146 mm (8.0" x 5.7")	
	Power	Input	DC +5V/+12V
Form Factor		AT/ATX support	
Compliance	CE, FCC ,RoHS		

ORDERING INFORMATION

EM-9560A EBC with Intel ULV Celeron 400MHz, Fan-less

EM-9560B EBC with Intel ULV Celeron 650MHz

PLATFORM ARCHITECTURE



About Lanner

Founded in 1986 and publicly listed (TAIEX 6245) since 2003, Lanner Electronics Inc. is an ISO 9001 certified designer and manufacturer of reliable, frontline security, storage and applied computing platforms and solutions. With headquarters in Taipei, Taiwan and branches in the U.S., India, and China, Lanner is uniquely positioned to deliver custom technical solutions with localized, value-added service.

Contact information

Lanner Electronics Inc
7F, 173, Section 2 Datong road
Sijhih City, Taipei County 221, Taiwan

T +886 2 86926060

F +886 2 86926101

E sales@lannerinc.com

W www.lannerinc.com