


FAB105 Quick Manual

5 Slot ATX-Support PICMG 1.3 Bus Passive Backplane with PCIe(16)/3x PCI Slot

I. Board Dimensions




FAB105 Quick Manual

5 Slot ATX –Support PICMG1.3 Bus Passive Backplane with PCIe(16)/3x PCI Slot

II.Connector

Connector	Description
CPU Slot	For PICMG 1.3 Full-Sized SBC
PClex16	For Additional PClex16 VGA card
PCI Slot	3xPCI Slot(33bit/33Mhz)
CN1	8 Pin Power Connector
PWR_BT1	Power Botton
HW_RST1	Reset
	24 Pin ATX Power Connector
	USB_1 Connector
	USB_2 Connector(optional function)

■ 8 Pin Power Connector-CN1




Notice:The 8 Pin Power connector could be used for Thermal Detected Board(For example.The AX8295A)


FAB105 Quick Manual

5 Slot ATX-Support PICMG 1.3 Bus Passive Backplane with PCIe(16)/3x PCI Slot


PWR_BT1 Connector



■ HW_RST1 Connector




■ USB1/USB2 Connector(Optional Function)



FAB105 Quick Manual

5 Slot ATX –Support PICMG1.3 Bus Passive Backplane with PCIe(16)/3x PCI Slot

■ 24-pin ATX Power Connector



Notice:The onboard 24 pin power connector also back compatible with 20 pin power supply

©Copyright 2001 by AXIOM Technology Co., Ltd.

All rights reserved.

March 2007, Version A1

Printed in Taiwan

9419B105010E

Trademarks Acknowledgments

AXIOM is a trademark of AXIOM Technology Co., Ltd.

Other brand names and trademarks are the properties and registered brands of their respective owners.

Specifications are subject to change without notice.