▶ English
▶ 繁體中文
▶ 简体中文

• about us   • download   • products   • contact us

Motherboard

GC693A

Download :

[Bios](#)

Driver

[Manual](#)

Specification:
Designed for Pentium III, Celeron II , Celeron & Cyrix III Processor by using VIA 693A/686A Chipset

- Support Intel Pentium III FCPGA, Celeron II, Celeron PPGA or Cyrix III Processor on Socket 370.
- VIA Apollo Pro Plus VT82C693A Chipset, Support 66/100/133 MHz Processor Front-side Bus.
- VIA VT82C686A Super South Bridge (not for +B option)
- VIA VT82C686B Super South Bridge (for +B option)
- Keyboard and PS/2 Mouse Wakeup
- Modem Ring Wakeup with External Modem
- Interface Header to Support Wake-On-LAN Enabled Ethernet Card
- Two 168-pins DIMMs, support up to 512MB Memory Capacity
- Support 133MHz SDRAM DIMM
- Support Virtual Channel Memory Technology
- 1x AGP Slot, 1x AMR Slot, 3x PCI Slots, 1x ISA Slot
- 1x FDD port, 1x LPT port, 2x COM ports
- 4x USB ports, 1x PS/2 mouse port, 1x IrDA Port
- Dual IDE channels supporting four Ultra-DMA 33/66 IDE devices
- Dual AT/ATX Power Supply Interface
- System Health Monitoring with Win98/95/NT Support
- Award 2Mbit BIOS, PC99/ACPI/DMI Compliant
- Baby AT Format, 220mm x 186mm PCB.
- Integrated with UltraDMA-100 IDE Capability (Model +B option)
- Enhanced with UltraDMA-100 IDE Capability with VT82C686B Super South Bridge
- Integrated AC97 Audio Onboard (Model +S option)
- AC97 2.1 Compliant Codec with 3D Stereo Enhancement
- SoundBlaster Pro Hardware for DOS Mode Compatibility
- Complete Driver Support for Win95/98/2000/NT
- 1x Line-out, 1x Line-in, 1x Mic-in
- 1x CD-in, 1x AUX-in, 1x Telephony Port, 1x Game Port

D-U-N-S Number 66-444-8631
Address: Rm 1017, Unit B, Focal Industrial Center, 21 Man Lok Street, Hunghom, Kowloon, Hong Kong.
Tel: (852) 2765-8368 Fax: (852) 2765-8772 E-mail: info@champion-first.com