

IP-4BDP22

Socket 478 PICMG Card for Pentium® 4 Mobile Processor with LCD / VGA / LAN

Key-point:

- > Socket 478 for Intel® Pentium® 4 Mobile Processor, up to 2.4GHz
- > Low profile heat sink with fan
- > Intel® 845D Chipsets, 400 MHz FSB
- > ATI® Mobility M6-D LCD / VGA function, Support dual CRT
- > Support 10/100 Base-TX Ethernet
- > 4 x USB ports / 2 x COM ports
- > WatchDog Timer, Hardware monitoring function & DOC



Specifications:

- ⊙ **Processor:**
 - * Intel® Socket 478 Pentium® 4 Mobile processor, Up to 2.4GHz
 - * Low profile heat sink with fan
- ⊙ **Core Logic:**
 - * Intel® 845D + ICH2 chipsets
- ⊙ **BIOS:**
 - * Award BIOS
- ⊙ **Front Side Bus Speed:**
 - * 400 MHz
- ⊙ **Memory:**
 - * Two 184-pins DIMM support 2GB DDR DRAM (max.)
- ⊙ **Onboard LCD / VGA Controller:**
 - * ATI® Mobility M6-D chip, on-die 16MB memory
 - * Support LVDS LCD panel & Dual CRT display
- ⊙ **LAN Controller:**
 - * Intel® 82562ET, for 10 / 100 Base-TX, Support wake up on LAN
- ⊙ **Onboard IDE:**
 - * Two EIDE channels for PIO Mode, DMA Mode
 - * Supports four ATA 100/66/33 IDE devices
- ⊙ **Multi I/O:**
 - Onboard Winbond® W83627HF chip, Support:
 - * 1 x IrDA by 5-pin pin-header
 - * 1 x Floppy Interface
 - * 1 x SPP / EPP / ECP parallel port by pin-header
 - * COM1 is RS-232
 - * COM2: RS-232 or RS-422/485 (jumper selectable)
- ⊙ **WatchDog Timer:**
 - * 256 Levels software programmable
- ⊙ **Keyboard / Mouse Connector:**
 - * 6-pins mini DIN for PS/2 type Keyboard & Mouse
 - * 1 x 5-pin header connector for external Keyboard
- ⊙ **USB:**
 - * Onboard 4 x USB ports by pin-headers
- ⊙ **SSD:**
 - * DIP socket supports M-System DiskOnChip® flash disks
- ⊙ **Hardware Monitoring:**
 - * Winbond® W83627HF chip, Monitoring for CPU and system temperature, voltage and fan speed
- ⊙ **Environments:**
 - * Operation temperature: 0°C to 60°C (32° F to 140° F)
 - * Storage temperature: -20°C to 80°C (-68° F to 176° F)
 - * Relative humidity: 10% to 90% (Non-Condensing)
- ⊙ **Certification:**
 - * CE, FCC Approval
- ⊙ **Form Factor:**
 - * Full Size, PICMG compliance
- ⊙ **Audio**
 - * No support
- ⊙ **PC-104 connector:**
 - * No support
- ⊙ **Others features**
 - * ITE® 8888 PCI to ISA bridge
- ⊙ **Dimensions (L x W):**
 - * 13.3" x 4.8" (338mm x 122mm)

*Specification is subject to change without prior notice

Ordering Information:

Model No.	Position	Support LCD	Support VGA	Support SCSI	Support LAN	Support Audio
IP-4BDP22	Standard Product	Yes	Yes	---	Yes	---

I/O Bracket Layout

