

PCI6AP2LX - [click here](#)

Processor:	Intel Pentium II 233-333 Mhz CPU
Chip set:	Intel 82440 LX PCI set
Expansion slots:	1XAGP (32 bit) slot (for 66/133 MHz AGP VGA adapter) 3X PCI (32 bit) slots. 3XISA (16 bit) slots.
System memory:	4X72 pins SIMM sockets (for FP/EDO DRAM module). 3X168 pin DIMM sockets for EDO/SDRAM mosule, up to 384 MB)
BIOS:	Award PCI BIOS with ACPI, DMI. Green PnP(Flash ROM for easy upgrade).
PCI IDE:	2XPCI Bus Master IDE ports (up to 4 IDE devices, including 120 MB IDE floppy). Supports Ultra DMA/33 function. Supports CD-ROM Boot Function.
I/O Interface:	Mouse supported. Floppy port (2 FDD supported, up to 2.88MB) 2 serial port (COM1/COM2, Two high speed UART port) 1 Parallel port (SPP/EPP/ECP supported) 2 USB port. IrDA TX/RX header
Power:	AT/ATX power connector (automatic detect)
Other Features:	LM 75 supports Fan status, CPU voltage music supported Warning music supported Supports 75 Mhz bus clock
Board Size:	AT form factor 33cmX22cm