

Processor:	Intel Pentium II 233-333 Mhz CPU
Chip set:	Intel 82440 LX PCI set
Expansion slots:	1XAGP (32 bit) slot (for 66/133 MHz AGP VGA adapter) 4X PCI (32 bit) slots. 3XISA (16 bit) slots.
System memory:	3X168 pin DIMM sockets for EDO/SDRAM mosule, up to 384 MB)
BIOS:	Award PCI BIOS with ACPI, DMI. Green PnP(Flash ROM for easy upgrade).
PCI IDE:	2XPCI Bus Master IDE ports (up to 4 IDE devices, including 120 MB IDE floppy). Supports Ultra DMA/33 function. Supports CD-ROM Boot Function.
I/O Interface:	PS/2 Keyboard/ Mouse supported 1 Floppy port (2 FDD supported, up to 2.88 MB) 2 serial ports (COM 1/ COM2, Two 16550 high speed UART ports 1 Parallel port (SPP/EPP/ECP supported) 2 USB port IrDA TX/RX header ATX double decker for I/O connector
Power:	AT/ATX power connector (automatic detect)
Other Features:	Automatic Switching Volatge Regulator LM 75 supports CPU temperature warming function Supports 75 MHz Bus Clock ACPI Power Management, Soft-Off control Supports Modem Ring-In & RTC Alarm Wake Up
Board Size:	ATX form factor 30.5cmX18.75cm