

# MSC-2700A



## Half size PCI bus Socket 479 Pentium-M SBC

Model No.	MSC-2700A	
Bus Architecture	PCI	
Processor	Socket 479,FC-PGA Intel Pentium-M/ Celeron-M	
CPU Speed	1.3 ~ 2.0 GHz (FSB 400MHz)	
Chipset	Intel 855GME + ICH4	
BIOS	Phoenix - Award	
RAM Size	Up to 1GB DDR333 SDRAM memory	
RAM Socket	1 × 184pin DIMM sockets	
I/O	On-board VGA	Support CRT, interface
	VGA Chipset	Built-in 855GME
	VDRAM	Share system memory
	Ethernet	LAN1 Intel 82562EM 10/100 Base-T
	Audio	AC97' Audio
	FDD Support	Up to × 2 floppy disk drives
	HDD Support	Support four EIDE devices with DMA33/66/100
	Serial Port	2 × RS232 ports
	Parallel Port	1 × SPP/EPP/ECP parallel port
	USB Port	6 × USB ports, USB 2.0 compliant
	PS/2 Port	1 × mini DIN connector with Y-cable support K/B and mouse
Watchdog Timer	256 levels	
PCB Size	Half-size	
PCB Dimension (WxD)	185mm × 122mm	
Environment	Operation 0°C to 60°C, Storage -20°C to 85°C; Humidity: 20% to 90%RH non-condensing	
Certification	CE and FCC Class A	
Order information	MSC-2700A: PCI socket 479 CPU card with VGA, Audio, LAN	



MiTAC Inc.

No.187 Tiding Blvd, Sec. 2, Neihu, Taipei City 114, Taiwan, R.O.C.

URL: <http://www.mitac.com.tw>

E-mail: [icp@mitac.com.tw](mailto:icp@mitac.com.tw)

Note: Specifications are subject to change without notice.

Last update 2006/3/2