

MSPC-8978

Support Intel Pentium III FC-PGA CPU

Specifications:

- **CPU** : Supports Intel 66Mhz Celeron and 100Mhz, 133Mhz FC-PGA CPU.
- **MEMORY** : Two DIMM sockets to support 100Mhz/133Mhz SDRAM/EDO 168-pin memory module.
- **BIOS**: AWARD PCI BIOS With Plug and Play, Green Function and Power Management function.
- **Intel 815e chipset**: GMCH, ICH2, FWH Chipsets Supports
 - ⊕ Pentium® III/ II Processor CPU 133/100/66MHz FSB **which boasts a 133MHz internal bus speed.**
 - ⊕ Built-in 3D Graphics with 4MB SDRAM Display Cache as Z-Buffer Supports Dynamic Display Memory Plus (DDM+) Technology
 - ⊕ Supports UltraDMA/100, AC '97, Low Pin Count I/O and integrates LAN controller
- **LAN Controller** : Intel 815e ICH2 integrated with **W82562EM** chip
- **Desktop Management Interface (DMI)** : Supports DMI through BIOS that allows hardware to communicate within a standard protocol creating a higher level of compatibility.
- **UltraDMA/100 IDE Ports** : Master UltraDMA/100 Bus IDE 80-pin Cable. Backward Compatible Legacy ATAPI Devices ATAPI IDE CD-ROM, CD-R, CD-RW, and LS-120
- **ECC function** : with Single Bit Error correction and Multiple Bit Error Detection.
- **Expansion Bus** : **PCI Rev.2.1.** 5V interface Compliant. **SMSC SLC88B17**, PCI-ISA Bridge Chip:
 - ⊕ support up to 5 ISA slot
 - ⊕ support full ISA at 1/4 of PCI frequency
- **On-Board I/O** :
 - 1 x FDD Port(up to 2.88M)
 - 2 x Serial Ports(16550 FAST UART Compatible)
 - 1 x EPP/ECP Parallel Port
 - IrDA TX/RX Header
 - Universal Serial Bus (USB) x 4
 - PS/2 Mouse & PS/2 KB Controller
- **H/W monitoring** : Winbond 83627HF I/O Chipset integrated, monitoring (positive, negative) Voltage, (CPU, System) Temperature and fan speed.
- **VGA** : Integrated in Chip (GMCH), 4MB on-board display cache for enhanced 3D performance
- **ATX power function** : build 4-pin ATX connector on board.

■ **Watchdog Timer:** Program setting available.

■ **Size :** 340mm x 122mm (11.3" x 4.8")

■ **PCB Layer :** 8-Layer PCB

