

P4PE-X/TE



ProArt

Gaming

Business

Mobile

Laptops

Displays /
Desktops

Motherboards /
Components

Networking /
IoT / Servers

Accessories

Support



Product Support For

P4PE-X/TE

[Find Another Model](#) >

Get Product Support

[Register Product](#)

CPU / Memory
Support

Driver & Utility

FAQ

Manual &
Document

CPU SUPPORT

CPU Support

Memory / Device Support

NEED HELP?

 [Email Us](#)

 [Find service locations](#)

The following table shows the supported CPUs for this motherboard [Click here to search other motherboards.](#)

CPU	Validated since PCB	Validated since BIOS	Note
Celeron 1.7 GHz (400 FSB, L2 cache:128KB)	ALL	ALL GO	
Celeron 1.8 GHz (400 FSB, L2 cache:128KB)	ALL	ALL GO	

P4PE-X/TE

Celeron 2.0 GHz (400 FSB, L2 cache:128KB)	ALL	ALL	GO
Celeron 2.1 GHz (400 FSB, L2 cache:128KB)	ALL	ALL	GO
Celeron 2.2 GHz (400 FSB, L2 cache:128KB)	ALL	ALL	GO
Celeron 2.3 GHz (400 FSB, L2 cache:128KB)	ALL	ALL	GO
Celeron 2.4 GHz (400 FSB, L2 cache:128KB)	ALL	ALL	GO
Celeron 2.5 GHz (400 FSB, L2 cache:128KB)	ALL	ALL	GO
Celeron 2.6 GHz (400 FSB, L2 cache:128KB)	ALL	ALL	GO

P4PE-X/TE

Celeron 2.7 GHz (400 FSB, L2 cache:128KB)	ALL	1004	GO
Celeron 2.8 GHz (400 FSB, L2 cache:128KB)	ALL	1004	GO
Celeron D 310 revE0(2.13 GHz, 533 FSB, Socket478)	2.00	1009.004	GO
Celeron D 310 revG0(2.13 GHz, 533 FSB, Socket478)	ALL	1009.004	GO
Celeron D 315 (2.26 GHz, 533 FSB, Socket478)	2.00	1009.003	GO
Celeron D 320 (2.4 GHz, 533 FSB, Socket478)	2.00	1008	GO

P4PE-X/TE

Celeron D 325 (2.53 GHz, 533 FSB, Socket478, revC0/D0)	2.00	1008	GO
Celeron D 325 (2.53 GHz, 533 FSB, Socket478, revE0)	2.00G	1009.006	GO
Celeron D 330 (2.66 GHz, 533 FSB, Socket478)	2.00	1008	GO
Celeron D 335 (2.8 GHz, 533 FSB, Socket478)	2.00	1008	GO
Celeron D 340 (2.93 GHz, 533 FSB, Socket478)	2.00	1008	GO

P4PE-X/TE

Celeron D 345 (3.06 GHz, 533 FSB, Socket478)	2.00	1008	GO
Celeron D 350 (3.20 GHz, 533 FSB, Socket478, revE0)	2.00	1009.003	GO
Celeron D 350 (3.20 GHz, 533 FSB, Socket478, revG1)	ALL	1009.006	GO
P4-1.6 GHz (Socket478, 400 FSB, L2 cache:256KB)	ALL	1002	GO
P4-1.6A GHz (Socket478, 400 FSB, L2 cache:512KB)	ALL	1002	GO
P4-1.7 GHz (Socket478, 400 FSB, L2 cache:256KB)	ALL	1002	GO

P4PE-X/TE

P4-1.8 GHz (Socket478, 400 FSB, L2 cache:256KB)	ALL	1002	GO
P4-1.8A GHz (Socket478, 400 FSB, L2 cache:512KB)	ALL	1002	GO
P4-1.9 GHz (Socket478, 400 FSB, L2 cache:256KB)	ALL	1002	GO
P4-2 GHz (Socket478, 400 FSB, L2 cache:256KB)	ALL	1002	GO
P4-2.20 GHz (400 FSB, L2 cache:512KB)	ALL	1002	GO
P4-2.26 GHz (533 FSB, L2 cache:512KB)	ALL	1002	GO
P4-2.40 GHz (400 FSB, L2 cache:512KB)	ALL	1002	GO

P4PE-X/TE

P4-2.40A GHz (533 FSB, L2 cache:1MB, 90nm)	2.00	1006	GO	
P4-2.40B GHz (533 FSB, L2 cache:512KB)	ALL	1002	GO	
P4-2.40C GHz (800 FSB, L2 cache:512KB, HT)	ALL	1002	GO	Please click on the limitation before target="_top" href="http://support.asus.com/tech no=747&SLanguage=en-us">L
P4-2.50 GHz (400 FSB, L2 cache:512KB)	ALL	1002	GO	
P4-2.53 GHz (533 FSB, L2 cache:512KB)	ALL	1002	GO	
P4-2.60 GHz (400 FSB, L2 cache:512KB)	ALL	1002	GO	

P4PE-X/TE

P4-2.60C GHz (800 FSB, L2 cache:512KB, HT)	ALL	1002	GO	Please click on the limitation before target="_top" href="http://support.asus.com/tech no=747&SLanguage=en-us">L
P4-2.66 GHz (533 FSB, L2 cache:512KB)	ALL	1002	GO	
P4-2.80 GHz (533 FSB, L2 cache:512KB)	ALL	1002	GO	
P4-2.80A GHz (533 FSB, L2 cache:1MB, 90nm)	2.00	1008	GO	
P4-2.80C GHz (800 FSB, L2 cache:512KB, HT, D1)	ALL	1002	GO	Please click on the limitation before target="_top" href="http://support.asus.com/tech no=747&SLanguage=en-us">L
P4-2A GHz (Socket478, 400 FSB, L2 cache:512KB)	ALL	1002	GO	

P4PE-X/TE

P4-3 GHz (800 FSB, L2 cache:512KB, HT, D1/M0)	ALL	1002	GO	Please click on the limitation before target="_top" href="http://support.asus.com/tech no=747&SLanguage=en-us">L
P4-3.06 GHz (533 FSB, L2 cache:512KB, HT, C1/D1)	ALL	1002	GO	
P4-3.20 GHz (800 FSB, L2 cache:512KB, HT, D1)	ALL	1002	GO	Please click on the limitation before target="_top" href="http://support.asus.com/tech no=747&SLanguage=en-us">L
P4-3.20 GHz Extreme Ed. (800 FSB, HT)	ALL	1003	GO	Please click on the limitation before target="_top" href="http://support.asus.com/tech no=747&SLanguage=en-us">L
P4-3.40 GHz (800 FSB, L2 cache:1MB, rev.G1)	ALL	1009.006	GO	
P4-3.40 GHz (800 FSB, L2 cache:512KB, HT, D1)	ALL	1003	GO	Please click on the limitation before target="_top" href="http://support.asus.com/tech no=747&SLanguage=en-us">L
P4-3.40 GHz Extreme Ed. (Socket478, 800 FSB, HT)	ALL	1003	GO	Please click on the limitation before target="_top" href="http://support.asus.com/tech no=747&SLanguage=en-us">L

P4PE-X/TE

Shop and Learn

Mobile	Accessories	Wired Networking
Phones	Motherboards / Components	Intelligent Robots
Accessories	Motherboards	AIoT & Industrial Solutions
Laptops	Graphics Cards	Servers
For Home	Gaming Cases	Smart Home
For Work	Cooling	Accessories
For Creators	Power Supply Units	Keyboards
For Students	Sound Cards	Mice and Mouse Pads
For Gaming	Optical Drives	Headsets and Audio
Accessories	Data Storage	Streaming Kits
Displays / Desktops	External Graphics Docks	Apparels Bags and Gears
Monitors	Networking / IoT / Servers	Cases and Protection
Projectors		WiFi Adapters and Chargers
All-in-One PCs	WiFi Routers	
Tower PCs	Whole Home Mesh WiFi System	
Gaming Tower PCs		

Learn More

Asus Design Center
ASUSPRO
Automotive Solutions

Support

Check Repair Status
Find Service Locations
Product Registration
Email Us
Call Us
Security Advisory
ASUS Support Videos
MyASUS

About Us

About ASUS
News
Investor Relations
About CSR for global
Press Room

Community



P4PE-X/TE

POWER BANKS

Controller

Gimbal