

P4S-X



ProArt

Gaming

Business

Mobile

Laptops

Displays /
Desktops

Motherboards /
Components

Networking /
IoT / Servers

Accessories

Support



Product Support For

P4S-X

[Find Another Model](#) >

Get Product Support

Register Product

CPU / Memory
Support

Driver & Utility

FAQ

Manual &
Document

CPU SUPPORT

CPU Support

Memory / Device Support

NEED HELP?

The following table shows the supported CPUs for this motherboard [Click here to search other motherboards.](#)

[Email Us](#)

[Find service locations](#)

CPU

Validated
since PCB

Validated since
BIOS

Note

Celeron 1.7 GHz (400 FSB, L2
cache:128KB)

All

All

GO

P4S-X

Celeron 1.8 GHz (400 FSB, L2 cache:128KB)	All		GO
Celeron 2.0 GHz (400 FSB, L2 cache:128KB)	All	All	GO
Celeron 2.1 GHz (400 FSB, L2 cache:128KB)	All	All	GO
Celeron 2.2 GHz (400 FSB, L2 cache:128KB)	All	All	GO
Celeron 2.3 GHz (400 FSB, L2 cache:128KB)	All	All	GO
Celeron 2.4 GHz (400 FSB, L2 cache:128KB)	All	All	GO
Celeron 2.5 GHz (400 FSB, L2 cache:128KB)	All	All	GO
Celeron 2.6 GHz (400 FSB, L2 cache:128KB)	All	All	GO
Celeron 2.7 GHz (400 FSB, L2 cache:128KB)	ALL	ALL	GO
Celeron 2.8 GHz (400 FSB, L2 cache:128KB)	ALL	ALL	GO
P4-1.4 GHz (Socket478, 400 FSB, L2 cache:256KB)	All	All	GO
P4-1.5 GHz (Socket478, 400 FSB, L2 cache:256KB)	All	All	GO
P4-1.6 GHz (Socket478, 400 FSB, L2 cache:256KB)	All	All	GO

P4S-X

P4-1.5 GHz (Socket478, 400 FSB, L2 cache:512KB)	All	All	GO
P4-1.7 GHz (Socket478, 400 FSB, L2 cache:256KB)	All	All	GO
P4-1.8 GHz (Socket478, 400 FSB, L2 cache:256KB)	All	All	GO
P4-1.8A GHz (Socket478, 400 FSB, L2 cache:512KB)	All	All	GO
P4-1.9 GHz (Socket478, 400 FSB, L2 cache:256KB)	All	All	GO
P4-2 GHz (Socket478, 400 FSB, L2 cache:256KB)	All	All	GO
P4-2.20 GHz (400 FSB, L2 cache:512KB)	All	All	GO
P4-2.26 GHz (533 FSB, L2 cache:512KB)	All	All	GO
P4-2.40 GHz (400 FSB, L2 cache:512KB)	All	All	GO
P4-2.40B GHz (533 FSB, L2 cache:512KB)	All	All	GO
P4-2.50 GHz (400 FSB, L2 cache:512KB)	All	All	GO
P4-2.53 GHz (533 FSB, L2 cache:512KB)	All	All	GO
P4-2.60 GHz (400 FSB, L2 cache:512KB)	All	All	GO

P4S-X

P4-2.80 GHz (Socket478, L2 cache:512KB)	All	GO
P4-2.80 GHz (533 FSB, L2 cache:512KB)	All	GO
P4-2A GHz (Socket478, 400 FSB, L2 cache:512KB)	All	GO



Shop and Learn

- Mobile
 - Phones
 - Accessories
 - Laptops
 - For Home
 - For Work
 - For Creators
 - For Students
 - For Gaming
 - Accessories
 - Displays / Desktops
 - Monitors
 - Projectors
 - All-in-One PCs
 - Tower PCs
 - Gaming Tower PCs
 - Mini PCs
- Workstations
 - Accessories
 - Motherboards / Components**
 - Motherboards
 - Graphics Cards
 - Gaming Cases
 - Cooling
 - Power Supply Units
 - Sound Cards
 - Optical Drives
 - Data Storage
 - External Graphics Docks
 - Networking / IoT / Servers**
 - WiFi Routers
 - Whole Home Mesh WiFi
- Wired Networking
 - Intelligent Robots
 - AIoT & Industrial Solutions
 - Servers
 - Smart Home
 - Accessories**
 - Keyboards
 - Mice and Mouse Pads
 - Headsets and Audio
 - Streaming Kits
 - Apparel Bags and Gear
 - Cases and Protection
 - Adapters and Chargers
 - Docks Dongles and Cable
 - Power Banks
 - Controller
 - Gimbal


Learn More

- Asus Design Center
- ASUSPRO
- Automotive Solutions
- AVC Licensing Notice
- Support**
- Check Repair Status
- Find Service Locations
- Product Registration
- Email Us
- Call Us
- Security Advisory
- ASUS Support Videos
- MyASUS

About Us

- About ASUS
- News
- Investor Relations
- About CSR for global
- Press Room
- ASUSTOR Inc.
- ASUS Cloud Corporation
- UniMax Electronics Inc.

Community



P4S-X