

http://pcchips.com/m70

Go

FEB APR SEP

◀ 25 ▶

1997 1998 1999



[4 captures](#)


14 Feb 1998 - 13 Oct 1999

▼ About this capture

M701

JUMPER SETTINGS

{ Data from M701 manual }



http://pcchips.com/m70

Go

FEB APR SEP

◀ 25 ▶


1997 1998 1999



[4 captures](#)

14 Feb 1998 - 13 Oct 1999

▼ About this capture



{ Data from M701 manual }


M701 Mainboard

JP15-CMOS RAM



Normal

Clear CMOS



JP2 -FlashROM Voltage Selectors

JP2 FlashROM Voltage Selector

Description

12 volt Flash ROM (2-3)

EPR0M and
5 volt Flash ROM (1-2)

JP2



(default)



JP4 - AT Bus Clock Selectors



PCI Clock/3



Note: CPU Speed=60MHz or 66MHz JP4 set to 1-2
CPU Speed=50MHz JP4 set to 2-3

JP3 Sleep Switch Connector

JP3 Sleep Switch Connector

Attach the sleep switch cable to this connector

Description


Normal Mode

Sleep Mode On

JP3



JP11, JP12 - CPU Speed Selector



CPU Speed			
Jumpers	66 MHz	60 MHz	50MHz
JP12			
JP11			

JP5, JP6, JP7 - CPU Internal Clock Speed Selectors

JP5, JP6, JP7 CPU Internal Clock Speed Selectors

Intel	JP5	JP6	JP7
x2.0			
x2.5			
x3			
x3.5			
x4.0			

Note: CPU Internal Clock Speed = External Input Clock x (table list) factor.

http://pcchips.com/m70

Go

FEB APR SEP



◀ 25 ▶



[4 captures](#)

14 Feb 1998 - 13 Oct 1999

1997 1998 1999

▼ About this capture

[\[M701 Specification\]](#)[\[M701 BIOS\]](#)[\[M701 JUMPER\]](#)

PCCHIPS Manufacturing Limited

*Unit 9, 2/Floor, Fook Hong Industrial Building,
19 Sheung Yuet Road, Kowloon Bay, Hong Kong.
Tel:(852) 2795 3890 Fax:(852) 2795 3179*

Modified: Nov 15 97 by Kevin Chan

