



• M741 MainBoard. *Key Features*

M741 Key Features

- The advanced features of the **SiS 620** mainboard include:
- Supports Pentium II 233-500 MHz and Celeron 266-433 MHz CPUs with frequency at 66/75/83/100MHz in Slot 1 for **Micro ATX** Form Factor
- Provides 3 DIMMs for SDRAM memory modules and is expandable up to 768 MB
- High performance 64bit **3D AGP** Graphics Accelerator with **8MB** frame buffer embedded in North bridge, Support **Windows98' Multiple Display** feature; AGP Rev.2.0 Spec. Compliant
- **3D PCI Sound Pro** on board, meet PC98' Spec., HRTF Positional Audio supports Microsoft's Direct Sound 3D, support driver for 3D game that used aureal software interface, with 4 channel speaker out; Software Wave-table Synthesizer, and 24 bit Digital Audio Interface (**SPDIF**) IN/OUT
- 2MB Flash ROM on board, provides complete Advance Configuration Power Interface (ACPI) and Legacy PMU; Ultra DMA 33/66; fully compliant with PC'97 and PC'98 Spec.
- Provides ATX power connector, supports various functions of ATX power such as Suspend/Shutdown, Alarm Wake-up, Modem Ring On, Wake On LAN and Interrupt Wake-up from Keyboard/Mouse and Keyboard Power On/Off
- Built-in **Hardware Monitor** circuit, supports thermal, power and fan speed monitor; supports Intel LANdesk Client Manager (LDCM)
- Bundled AMI **Desktop Client Manager** for detecting abnormal condition and thermal automatically or management through the Network link.
- Provides Digital Audio Cable set with AUX IN/OUT and SPDIF IN/OUT interface for your home theater application

- Provides Trend Micro's ChipAwayVirus and PC-cillin (OEM) for Windows 95/98 and the Internet virus protection

Trademarks and/or registered trademarks are the properties of their registered owners

This specification is subject to change without notice.

Modified: April 10 99
