





Socket 370 P-III CPU Card w/ VGA/2LAN



Prox-1616 with VGA, w/o2 LAN
Prox-1618 with VGA,1 LAN



CPU Type: Intel® Celeron™/P-III /Tualatin processors
 CPU Voltage: Auto detect
 CPU Frequency: 566 GHz ~ 1.X GHz& up reserved
 Chipset: Intel® 815E Chipset with GMCH, ICH2, FWH
 Power Requirement: Support AT/ATX backplane, 10-pin ATX connector on board +5V and +12V
 DRAM: 1 x 168-pin DIMM up to 256 MB
 Cache: Built-in CPU
 BIOS: Award PnP BIOS, Firmware HUB Bios 4MB, with VGA BIOS
 I/O Chipset: ICH2 & LPC
 IDE Interface: 1 x EIDE (UDMA-/33/66/100), 1xCF
 FDD Interface: 1
 Serial Port: 2 x 16550 UART, COM2 for RS232/422/485
 Parallel Port: 1 x parallel (SPP/EPP/ECP)
 Watchdog: 16 level Watchdog Timer selectable w/Reset/NMI
 CMOS: Built-in ICH2, battery backup
 Keyboard: Mini DIN connector & external connector
 Mouse: Mini DIN connector (selectable w/ keyboard)
 Speaker: Internal buzzer & external speaker connector
 VGA: Built-in GMCH, max. 64M shared memory for CRT & LCD
 LAN: Intel 82559 & 82562ET PHY, 10/100 Base-TX Ethernet, 2 x RJ-45, support Wake-on-LAN
 USB: 2 x USB 1.1
 Bus Interface: PCI Bus
 Hardware Monitor: Voltage, CPU temp. & cooling fan

Green Function: Controlled by hardware & software

Dimension: 185mm x 122mm, 7.28" x 4.8"