www.arima.com.tw/server

AMD® Opteron™ Socket-F SW44X1U Series Barebone/System

Model	SW44X1U
Chassis Model	RM13907
Color	Black
Dimension (D*W*H)	660 x 430 x 43.5mm, 26 x 16.9 x 1.7"
Integrated Board	SW440 / SW442 *
Power Supply	500W with Active PFC
Backplane	SATA II
Peripheral Drives	
Slim ODD	Slim DVDROM
Drive Bays	
Hot-swappable	4
Cold-swappable	N/A
LED Indicator	
System Power On/Off	1
System error	1
UID	1
HDD LED	2 on each HDD tray
NIC Link/Activity	2
Fan Fail	1
Infiniband Link/Activity	N/A
Switches/ Controls	
Power On/Off	1
System Reset button	1
Alert Reset button	1
USB 2.0	1
Riser Card	
Default	1 x PCI-E(x8) slot
Option 1	N/A
Option 2	N/A
System Management	
OPMA card (IPMI 2.0)	Scorpio 2 / Aquarius *
Fan speed control	V
Fan failure alert	V
System fault	V
UID	V
Chassis Intrusion detect	V
Rear I/O	
VGA,KB,MS	3
Serial Port	1
Parallel Port	N/A
USB 2.0	2
LAN	3 (1 dedicated for OPMA)
SCSI	N/A
SAS	N/A
Infiniband	N/A
Fan	
Middle (Non-hotswap)	5 x 40mm
Rear(Non-hotswap)	1 x 40mm

Arima reserves the right to change specifications or other product information without notice.
* - Optional

Dealer Stamp