The Wayback Machine - https://web.archive.org/web/19981205184955/http://www.mycomp-tmc.com:80/TD6…

TD6NFK
Dual Pentium II 440FX Motherboard with ATX Form Factor



Processor Socket	Two Slot 1
Processor	Dual Pentium II, up to 300MHz
Chipset	Intel 440FX PCIset with IOAPIC
L2 Cache	L2 cache integrated in the CPU
BIOS	DMI 2.0, Plug and Play
System Memory	Memory Capacity: 1GB Memory Sockets: Eight 72-pin SIMMs Memory Type: EDO Data Integrity: ECC/Parity Checking
Power Management	ACPI
Onboard IDE	Supports PIO Mode 0-4, DMA Mode 0-2 Two channels for up to 4 IDE devices Bus Master Ultra DMA/33
Onboard I/O	SMC 37C669 with: One floppy controller Two 16550 UART compatible serial ports One ECP/EPP parallel port
H/W Monitoring (stuffing option)	NS LM-78 H/W monitoring ASIC and LM-75 thermal sensor for: Temperature monitoring Voltage monitoring Fan failure detection
USB	Two onboard USB headers
IrDA Interface	Onboard infrared header
Keyboard & Mouse	Onboard 6-pin mini DIN PS/2 keyboard connector Onboard PS/2 mouse connector
Expansion Slots	Five 32-bit PCI slots Two 16-bit ISA slots
Form Factor	ATX Form Factor 12" x 9.6"

Copyright 1996 Taiwan Mycomp Co, Ltd. All Rights Reserved. Pentium II, Pentium/MMX and Pentium Pro are registered trademarks of Intel Corp. All other product and brand names are trademarks and/or registered trademarks of their respective companies.